

# Green Stormwater Infrastructure Survey & Drawing Standards

**Version 3.1** May 2021



# **Table of Contents**

What	s's New		3
1.0	Introduct	ion	4
2.0	SURVEY (	GUIDELINES	5
2.1	Detailed	Survey Requirements	5
2.2	Drainage	Area Information Survey Requirements	12
3.0	DRAWING	G REQUIREMENTS	13
3.1	General F	Requirements	13
3.2	Symbolog	gy & Labeling	16
3.3	Dimensio	ns & Elevations	18
3.4	Landscap	e Plans	18
4.0	CAD STAI	NDARDS	20
4.1	CAD Platf	forms to Utilize	20
4.2	Template	PS	20
4.3	Graphic (	Concepts and Standards	21
4.4	Deliverab	oles and Data Exchange	23
4.5	File Nami	ing Convention and Standard Reference Files	24
4.6	Layer Na	ming Convention	24
Appe	ndix A.	Callout and Block Library	
Appe	ndix B.	Linetypes and Hatching	
Appe	ndix C.	Lettering Standards and Text, Multileader, Dimension and Table Styles	
Appe	ndix D.	Dynamic Block Functions	
Appe	ndix E.	Recommended Drafting Tips	
Appe	ndix F.	Example Plans	

# What's New

Effective Date: January 2021 – Additional updates from May 2021 noted with an asterisk (\*)

Revisions History: Listed below are the major changes that occurred between the 2018 version of the GSI Survey & Drawing Standards and this most recent 2021 version.

### 1.0 INTRODUCTION

• Clarified that water/sewer sheets added to a GSI planset should still follow Water/Sewer standards.

### 2.0 SURVEY GUIDELINES

- Added ponding in ROW to list of items to look out for when making field observations.
- Clarified that pavement markings should reflect the width/thickness measured in the field.
- Clarified that roadway paving material should only be called out if it differs from asphalt.
- Added trash cans, planter boxes, and bike racks to example list of street furniture to be identified.
- Added requirement to show downspouts if proposed system is located in adjacent ROW.
- Clarified that abandoned utilities and stubbed laterals should be shown if in the detailed survey area rather than "in the vicinity of proposed system".
- Cross-sections are only needed at proposed green inlet locations based on proposed system layouts in planning package, rather than upstream of all existing inlets.

### **3.0 DRAWING REQUIREMENTS**

- "Centralized GSI Facility" replaced "Large Area Disconnection" terminology.
- Clarified that components in elevation views should be drafted relative to the street center line.
- Added requirement to show 2V:1H sewer zone of influence line as well as the projection lines that
  define limits of impermeable geomembrane liner in cross sections and profile/elevation views.
   These lines should be removed at PS&E and Final Design phase.
- Added guidance to not show overhead wires on G sheets (only baseplan and landscape sheets).
- Added guidance that abandoned utilities and stubbed laterals may be removed from design plans if they make the plan too crowded and are located outside of proposed area of excavation.
- In order to avoid having to make later edits, Maintenance Component ID numbers are now assigned by GSO during PS&E design review after PWD project manager confirms components are finalized.
- Removed common required elevation callouts and instead referred to Appendix A.
- Added guidance to include dimensions of horizontal offsets from existing street features that impact the location for proposed work.
- Added guidance that tree blocks should not be used for tree trenches on landscape plans.
- "Tree Location ID" replaced "Tree Pit ID" terminology. Updated Tree Location ID labeling guidance\*
- Updated guidance on how varying soil depth should be depicted on G-series sheets.\*

### **4.0 CAD STANDARDS**

- Updated file sharing guidance.
- Converted color-based plot style to a style-based plot style.
- Updated baseplan and design callout libraries.
- Revised existing linetypes and hatches.
- Updated block library with revisions to existing blocks and additional blocks.
- Updated example plans to reflect current drawing standards. Updates included replacing some plans to present more typical scenarios.

# 1.0 INTRODUCTION

This resource provides standardized survey, drawing, and Computer Aided Design (CAD) requirements that must be used when drafting contract plans for all Green Stormwater Infrastructure (GSI) projects funded and/or maintained by the Philadelphia Water Department (PWD). The following information is to be used throughout the design process by PWD staff, providers of professional engineering services contracted by PWD, and other agencies/partner organizations that are working with the Department. All PWD GSI drawings must, at a minimum, meet the standards outlined within this document.

### **Part One**

Details the requirements for GSI surveys and baseplans. Survey work is divided into two general categories:

- **Detailed Survey** Provides requirements for surveying on-street and off-street locations where GSI will be installed. Survey includes collecting detailed information about surface elevations, underground utilities, and surface features.
- Drainage Area Information Survey Provides requirements for gathering information about
  the drainage areas contributing to GSI systems. Survey includes combining City Plan
  Information with minimal surface elevation information to delineate the terminating points
  of the contributing drainage area.

### **Part Two**

Includes an overview of general drawing requirements that should apply to all projects including specific guidance on system/SMP numbering, maintenance component IDs, and drafting landscape plans.

### **Part Three**

Provides all necessary information for using the GSI CAD Standards. The GSI CAD Standards include drafting standards, templates, standard callouts, and block libraries to standardize GSI drawings provided by GSI Unit Design Consultants.

### **Appendices**

Provides all standard callouts, line types, lettering standards, and block libraries as well as example plans to illustrate the requirements of sheet layout, design plans, and landscape plans.



### Note on Water & Sewer Standards:

This resource builds on standards defined in the PWD Department *Water & Sewer Design Manual*. Design professionals working on PWD GSI may find it useful to familiarize themselves with the *Water & Sewer Design Manual* sections on **Contract Drawings** and **Drawing Standards**. Water/sewer sheets added to a GSI work number should follow Water & Sewer standards.

http://www.phillywaterdesign.org

# 2.0 SURVEY GUIDELINES

# 2.1 Detailed Survey Requirements

### 2.1.1 On-Street Extents & Elevations

- 1. Provide spot elevations for the houseline or protruding feature (steps, window wells, etc), top of curb, bottom of curb, and centerline for both sides of the street taken at 25-foot horizontal intervals.
- 2. Provide sufficient spot elevations at corners where ADA ramp replacement may be required.
- 3. Provide sufficient spot elevations for sidewalk grading plans for bumpout systems. See *Streets Design Guidance for GSI Projects*.
- 4. Where there is an obvious localized sump, provide, at a minimum, labeled spot elevations for the centerline, building line, top of curb, and bottom of curb for both sides of the street to adequately define the sumped area.
- 5. Provide labeled elevations for the point of curvature (PC), point of intersection (PI), and point of tangency (PT) at both the bottom and top of curb at intersections.
- 6. Extend the survey a minimum of 50 feet (horizontal) up both sides of any intersecting streets or alleys in either direction.
- 7. Show one (1) foot contours on baseplans. Contours may ultimately be removed from final design plans to improve plan clarity.
- 8. Survey locations for existing features as described in the following sections.

### 2.1.2 Off-Street Extents & Elevations

- 1. Provide spot elevations on a 25-foot grid, or as necessary to provide ½ foot contours, extending 50 feet horizontal outside the Detailed Survey area identified by PWD.
- 2. Ensure that the survey is tied into an adjacent intersection between two cartways or a cartway and a facility entrance.
- 3. Show ½ foot contours on baseplans. Contours may ultimately be removed from final design plans to improve plan clarity.
- 4. Provide surveyed locations for existing features as described in the following sections.

### 2.1.3 City Plan Information

- 1. Show curb and right-of-way (ROW) lines from City Plan. Where the curb differs from City Plan or does not exist, show the City Plan curb line as a dashed line.
- 2. Label the extents of ROW distance and angles.
- 3. Label block lengths/distances. Label should be placed adjacent to the ROW line.
- 4. Label all street grades, with label shown along the gutter.
- 5. Include cartway and footway width dimensions in both plan and section views.
- 6. Label street, including State Route numbers (SR#'s). If the street is not legally open, label as such in the street callout.
- 7. Label City Plan elevations at all corners and mid-block change in grades.
- 8. Place arrow heads on the curb pointing in the direction of stormwater surface flow.

### 2.1.4 Plan View Information

<u>Field Observations</u> – The final design is dependent on the information obtained during field investigations. Designers who visit the field locations should pay special attention to the visible details of the site which may be useful in making design decisions later. Examples of such items are:

- ✓ Condition of paving, signs of paving disruptions, deterioration, etc. This information will assist in establishing appropriate paving limits.
- ✓ Ponding in ROW.
- ✓ Potential construction interferences such as low bridges, tree interference, overhead wires or structures, downspouts disconnected to the ROW, etc.
- ✓ Condition of buildings (vacant, collapsing, etc.)
- ✓ Neighborhood gardens and landscaped areas

### Benchmarks

- a. List the benchmark obtained from the Streets Department Survey District in the upper right-hand corner.
- b. If the obtained benchmark is more than one turning point away from the proposed work, then a local benchmark should be set. The local benchmark should be outside of the proposed limit of disturbance and on a permanent structure. The local benchmark should be listed in addition to the benchmark obtained from the Streets Department Survey
  District.
- c. Drill holes should be avoided when setting a benchmark and manhole rims should not be cited as benchmarks unless identified by chisel cut markings and outside of vehicular travel lanes.

### 2. Right-of-Way Information

- a. Place the name of the main street along the top of the sheet without using abbreviations.
- b. Draft pavement markings to reflect the width/thickness measured in the field.
- c. Abbreviate the words street, road, avenue, etc. on intersecting streets.
- d. In the street label, show the direction of traffic along with parking and bike lane information on all streets including intersecting streets.
- e. Use District Standard Measurement for all distances.
- f. Show all overhead bridges and the elevation of the underside of bridges.

### 3. Paving Information

- a. Identify the materials for the roadway, footway, and curb. Roadway paving material should only be called out if it differs from asphalt.
- b. Show depressed curbs and driveways.
- c. Indicate deteriorated footways and curbing.
- d. Ensure that any special patterns for the footway are identified.
- e. Label any obvious areas with drainage problems due to paving.

### 4. Existing Features

- a. Identify all fences and walls and note the height and material.
- b. Identify all steps, cellar doors, fire hydrants, parking meters, manhole covers, traffic signs and signals, stop signs, 20 ft. sign poles, utility poles, and all street furniture (phone booths, mailboxes, benches, trash cans, planter boxes, bike racks, etc.).
- c. Identify any landscaped areas, and, if available, the owner (i.e. community garden sign).
- d. Show all existing curb stops, sewer vent boxes, and gas valves.

### 5. Property Information

- a. Indicate all properties and adjacent properties with street addresses and property lines.
- b. Provide a general outline for all structures.
- c. Provide general building information including use and construction (i.e. 3-story, brick, school).
- d. Indicate where the interior of the property differs in elevation from the adjacent ROW by listing the change in elevation as a positive or negative.
- e. Provide a general use and ground cover for properties without buildings (i.e. grass, park, garden, etc.).
- f. Identify where property is vacant.
- g. Show all gates, driveways, access points, etc. for properties.
- h. Show downspouts if proposed system is located in adjacent ROW.

### 6. Trees

- a. Label diameter at breast height (DBH) of all existing trees inside of the survey area.
- b. Scale tree symbol to show the actual size of the tree canopy, but do not move point for trunk of tree when doing this. Canopies can be determined using aerials.
- c. Show canopies that reach over into the survey area.
- d. Trees adjacent to work within the LOD should either be listed as To Be Removed, or To Be Preserved. Trees being preserved should follow construction tree protection guidance listed in Chapter 5: Landscape Design Requirements of the <u>GSI Landscape Design</u> <u>Guidebook</u>.




Figure 1 – Example of Tree Canopy on Plans

### 2.1.5 Utility Information

### **Note on Utility Location:**

If record drawings are not available from the property owner, then field testing, Ground Penetrating Radar (GPR), Closed-Circuit Television (CCTV), or Cable Avoidance Tool and Signal Generator (CAT and Genny) may be utilized to locate and inspect on-site underground private utilities.

- 1. Identify all existing utilities with owner, size, and cover.
- 2. List size by diameter or width x height.
- 3. Dimension all utilities from the curb line to the center line of the utility. Offset from the curb is to vary consistently between dimensions.
- 4. Show utilities as a double line when their width is 42 inches or greater, other than existing water and sewer as noted below.
  - a. All water mains 24 inches or greater in diameter...Double line.
  - b. Sewers with a width of over 21 inches...Double line with a center dimension line.
  - c. Brick sewers... Double line with a center dimension line.
  - d. Stormwater sewers ... Double line with a center dimension line.
- 5. Show all abandoned utilities in the detailed survey area.
- 6. Show SEPTA and railroad tracks as accurately as possible, but not dimensioned. List their status (active, inactive, or paved over).

### **Note on Paved Over SEPTA Trolley Tracks:**

SEPTA does not provide information through PA One Call for trolley tracks that have been paved over. Designers will need to use the Highway Supervisor Plans to get this information.

- 7. Sewer list pipe size as height x width and as follows:
  - a. Brick sewers...Feet and inches (e.g. 2'-6" x 1'-8").
  - b. Reinforced concrete pipe...Inches (e.g. 36" RCP).
  - c. Box sewers (any material)...Feet and inches.
  - d. Callout all existing sewer manholes including the first manhole on each connecting sewer with a field invert, rim elevation, and owner if not PWD.
  - e. Show existing laterals over six (6) inches in diameter with the lateral size and material, where information is available.
  - f. Show abandoned or unused laterals "stubbed laterals" in the detailed survey area. Stubbed laterals can be identified on the sewer return plans by lines drawn perpendicular to the sewer which stop at the curb line and which cannot be verified as active laterals (no apparent vent box).

- 8. Inlets Collect inlet information as follows:
  - a. Type
  - b. Top elevation (grate elevation for HWG and OMG inlets, top and bottom of curb elevations for City inlets)
  - c. Invert elevation of lateral to sewer
  - d. If inlet is owned by an entity other than PWD, callout the owner.
  - e. Note if inlet has a brick catch-basin.




Figure 2 – Survey information for Inlets

### **Inlet Survey Tips:**

If inlets are completely clogged, work with the PWD project manager to submit an inlet cleaning request. PWD work number and PWD project manager should be included on all requests. Inlets with some trash/debris should still be able to be surveyed using these tips.

### **Trap Door Measurement**

If the inlet is constructed with a metal trap and trap door, the depth of the inlet lateral invert can be obtained by measuring from the top of the dripstone (BC) to the bottom of the trap door. As shown in *Figure 3* below, the bottom of the trap door is the same elevation as the lateral invert. Unless an inlet is experiencing operational issues preventing the lateral pipe from conveying stormwater, the water level in this type of inlet should always be at or below the bottom of the trap door.




Figure 3 – Inlet with Cast Trap and Cast Trap Standard Details

### **Catch Basin Depth Measurement**

If the inlet is constructed with a solid trap wall, the lateral invert depth must be estimated by calculating its depth based on a measurement to the bottom of the catch basin. An estimated depth is used because measuring the exact inlet lateral invert depth would require removal of the trap wall. This method employs a tool for locating the bottom of the inlet catch basin and a tape measure for gathering the depth measurement. When locating the catch basin bottom, PWD Inlet Cleaning uses a long rigid pole to push through any floatables and grit accumulated in the catch basin.

- 1. Locate and measure depth to catch basin bottom Extend the measuring tool as deep into the inlet catch basin as possible. It is possible that floatable debris and grit may be within the catch basin and require some application of force to reach the catch basin bottom. After noting the point along this pole where the top of the dripstone (BC) is, remove the pole from the inlet and measure the
  - distance between the end and that point. The measured distance will be the depth to the catch basin bottom.
- 2. Calculate the estimated depth of the inlet lateral invert From the depth to the catch basin bottom the inlet lateral invert depth can be estimated by subtracting twenty-two inches (22"). This estimated difference between the catch basin bottom and the inlet lateral invert was determined by PWD Inlet Cleaning after taking a series of measurements at various inlets around the City and should be considered an estimate only.




Figure 4 – Inlet with Solid Trap Wall Standard Detail

### 2.1.6 Cross Sections for On-Street Surveys

- 1. A cross section is needed at proposed green inlet locations based on proposed system layouts in planning package. Typically, this is five (5) feet upstream of an existing inlet.
- 2. Show all utilities in the entire cartway and both footways to the house lines. Show all abandoned utilities as well.
- 3. Show adjacent slopes or walls in the cross section.
- 4. Show basement depth of adjacent properties in cross sections. Assume 8-foot depth for the properties with unknown basement depth.
- 5. Where there is a railroad bridge shown on the baseplan, show a cross section of the railroad bridge with underside elevations on the baseplan (this is in addition to the standard cross section for the baseplan).
- 6. City Plan information, where it deviates from existing, should be shown with a dashed line.

# 2.2 Drainage Area Information Survey Requirements

### 2.2.1 Extents & Elevations

- 1. Drainage area information may be gathered either by survey or by City Plan information without field survey, depending on the availability of information.
- 2. Survey may be required where City Plan is not available electronically or where actual elevations differ from City Plan by more than six (6) inches. Where survey information is used:
  - a. Collect sufficient information to determine the limits of the contributing drainage area.
  - b. Continue at least 50 feet in all direction past the limits of the contributing drainage area.
  - b. Provide surveyed locations for existing features as described below.
  - c. List the survey benchmark in the upper corner obtained from the Streets Department Survey District.

### 2.2.2 City Plan Information

- 1. Show curb and right-of-way (ROW) lines from City Plan. Where the curb differs from City Plan or does not exist, show the City Plan curb line as a dashed line.
- 2. Label the extents of ROW distance and angles.
- 3. Label block lengths/distances. Label should be placed adjacent to the ROW line.
- 4. Label all street grades, with label shown along the gutter.
- 5. Include cartway and footway width dimensions in both plan and sections.
- 6. Label street, including State Route numbers. If the street is not legally open, reflect in the street callout.
- 7. City Plan elevations at all corners and mid-block change in grades.
  - a. Assume the survey elevations are to City Plan if the existing elevations are within six (6) inches of the City Plan data.
  - b. If the survey elevations are different than City Plan by more than six (6) inches, show both the existing street elevation and City Plan elevations.
  - c. Place arrow heads on the curb pointing in the direction of stormwater flow.

### 2.2.3 End of Drainage Area Information

- 1. Identify the feature that terminates the drainage area with an appropriate callout such as "END OF DRAINAGE AREA: RIDGE".
- 2. Identify a mid-block high point with labeled elevations for both the top of curb and gutter for both sides of the cartway.
  - a. At a 25-foot offset to either side of this high point, provide labeled elevations for both the top of curb and gutter elevations for both sides of the cartway.
  - b. Callout the mid-block high point as "END OF DRAINAGE AREA: MID BLOCK HIGH POINT".
  - c. Include high point as a spot elevation if separate from the centerline of the street.
- 3. Identify any inlet that terminates the drainage area with the inlet type and labeled elevations for both the top of curb and gutter at the inlet.
  - a. If at the end of a block, ensure that both the inlet and the entire intersection are shown.
  - b. Callout the inlet as "END OF DRAINAGE AREA: INLET".

### Field Observations – Look out for:

- ✓ Signs of significant ponding due to paving or curbing deterioration.
- ✓ Large contributing drainage areas such as parking lots or adjacent impervious surfaces.

# 3.0 DRAWING REQUIREMENTS

### 3.1 General Requirements

### 3.1.1 Drawing Size

- 1. All drawings must be on 30"x42" paper and conform to the *PWD Water & Sewer Design Manual* requirements except where noted below. See *Appendix F* for example plans.
  - a. Sheet...30" x 42"
  - b. Outer Border...29" x 41" (1/2" from top, bottom, right, and left)
  - c. Inside Border...27" x 39" (1" from top, bottom, right, and left)
  - d. Title Block...5" x 9" in lower right corner

### 3.1.2 Drawing Scales

- 1. Draft the location plans at an appropriate scale to fit the site content and maintain legibility.
- 2. Draft the baseplans at a 1"=10' scale, as detailed site plans are required to be submitted at this scale, or as approved by the PWD project manager. Sheets should be cut in a manner consistent with proposed systems layouts to reduce the setup of the project sheets.
  - a. <u>Exception</u>: Centralized GSI Facility projects may be drafted at a different scale. Generally, scales should be no smaller than 1:30 for legibility.
- 3. Draft the landscape plans at a scale no greater than 1"=10' (so the detail of the planting design can be easily readable), unless otherwise specified by the PWD project manager. 1/4"=1' is acceptable for smaller systems such as planters or bumpouts as long as the viewport shows enough contextual information to identify the location of the SMP. Each system should be shown on its own sheet with its corresponding plant schedule. Do not combine more than one system on a sheet or have one single plant schedule for multiple systems.
- 4. Draft the sections at a 1/4 " = 1'-0" scale or as otherwise appropriate and as approved by the PWD project manager.
- 5. Draft the profiles/elevation views at a 1"=5' vertical scale and a 1"=10' horizontal scale or as otherwise appropriate and as approved by the PWD project manager.

### 3.1.3 Plan Presentation

- 1. The Design Consultant's name or company logo should be included to the left of the title block on each sheet.
- 2. List the completion date directly below the Design Consultant's company name or logo. At each submission ensure that this date is updated to aid in version tracking.
- 3. During design development, label plans in accordance with their design phase:
  - a. Preliminary Design
  - b. Substantially Complete Design
  - c. Pre-Final Design
- 4. Final plans are to be stamped by a registered Professional Engineer in the State of Pennsylvania.
- 5. Provide the following on each drawing above the title block as shown in the *PWD Water & Sewer Design Manual*:
  - a. Ward number
  - b. Sewer Plat Number
  - c. Highway District Number
  - d. Streets Survey District Number

- e. One Call Serial Number
- f. Outfall Number (if applicable)
- 6. Work numbers are to conform to the requirements outlined in *Section 1 Project Initiation* of the *PWD Water & Sewer Design Manual*. For GSI projects, work numbers should be given the prefix of (S) and the suffix of (G), for example: S-50100-G.
- 7. Page numbers are to be as follows:
  - a. T Index Sheet
  - b. G Green Sheets including plan, section, and profile views and all detail sheets
  - c. L Landscape Sheets including details (may not be part of final bid set\*)
  - d. DA Drainage Area Sheets (not for construction\*)
- 8. In plan view, orient the primary street horizontally across the sheet, with the north arrow oriented up in reference to the horizontal line.
- 9. Show connecting plan sheets with appropriate use of match lines.
- 10. Proposed legend must be included on all sheets.
- 11. Plan view, sections, and profiles/elevation views should generally be included on the same sheet for all systems.
- 12. For elevation views, which show a system in profile but include system components at multiple layers, the components should be drafted relative to the street center line.
- 13. For centralized GSI facility projects, order GSI sewer sheets such that they follow the flow pattern of the sewer to the GSI system.
- 13. Include a representative cross-section for every system and at all street crossings. Sections should ideally be located at the deeper end of system, particularly when located adjacent to structures, or where there are complicated configurations.
- 14. Show basement depth of adjacent properties in cross sections. Assume 8-foot depth for the properties with unknown basement depth. The bottom of property and its respective bearing zone should be removed at PS&E and Final Design phase.
- 15. In cross sections and profile/elevation views, show 2V:1H sewer zone of influence line as well as the projection lines that define limits of impermeable geomembrane liner. These lines should be removed at PS&E and Final Design phase.
- 15. Confirm location of section with PWD project manager prior to drafting.
- 16. Show actual ADA ramp location and design layout submitted to Streets Department ADA Unit including accurate placement of detectable warning surface (DWS) and landing area.
- 17. Show geomembrane liner and geotextile configuration of the system in plan and section views. Profile/elevation views should not show any information on liner/geotextile.
- 18. Do not show overhead wires on G sheets. Should only be on baseplan and landscape sheets.
- 19. Abandoned utilities and stubbed laterals may be removed from design plans if they make the plan too crowded and are located outside of proposed area of excavation. Confirm with PWD project manager before removing.

### **Note on Plan Clarity:**

Designers should attempt to minimize overall plan clutter on all sheets. Particular attention should be paid to overlapping lines, text, and symbols. In cases where the proposed callouts are difficult to read, drafters should utilize background masking.

### **Note on Landscape Plans and Drainage Area Sheets:**

PWD typically completes landscaping through a separate landscaping contract. If landscaping is done by this separate contract, then the landscape plans should not be part of the construction documents for the general construction project. Instead, the landscape plans should be provided as a separate drawing set and should not be included in the numbering of the general bid set.

Drainage Area sheets are required for PWD reference and are integrated into PWD's GIS asset tracking system. However, Drainage Area sheets are not part of the construction drawings and should not be included in the numbering of the general bid set.

# 3.2 Symbology & Labeling

### 3.2.1 General

- 1. Standard PWD GSI symbols and labeling must be used to the maximum extent feasible. See *Sections 3.2.2* and *3.2.3* below and *Appendix A*.
- 2. If features are owned and/or maintained by entities other than PWD, ownership must be added to all relevant callouts or otherwise distinguished through a note on the plans.

### 3.2.2 System & SMP Numbering

PWD uses a unique numbering methodology to identify GSI assets. The numbering begins on the design plans and in the design metrics report and is carried over to PWD's GIS asset tracking system and green metrics tracking database (GreenIT).

- 1. System labels are composed of the project ID and the system number in the format: [Project ID]- [System Number].
- 2. SMP labels are composed of the SMP type, the project ID, system number, and SMP number in the format: [SMP Type] [Project ID]-[System Number]-[SMP Number].
- 3. SMP types included in the labeling must conform to PWD's standard list of SMP types defined in the *GreenIT Design Report Definitions*.
- 4. Labels should be bold and prominently displayed. See example in Figure 5 below.





Figure 5 – Example SMP and system labels

### 3.2.3 Maintenance Component IDs

PWD uses a unique numbering methodology to identify GSI components, such as inlets, pipes, cleanouts, observation wells, and other structures. Similar to the system and SMP numbering, the component IDs are subsequently carried over to PWD's GIS asset tracking system. See *Appendix A* for templates of component ID callouts. *Figure 6* below provides an example of how these IDs are presented on a design plan.

- 1. The Design Consultant should show an empty component ID table on the Preliminary Design, Substantially Complete Design, and first PS&E Design submissions.
- 2. Numbers are assigned by the PWD Green Stormwater Operations (GSO) Group. GSO marks up the design plans with the appropriate component IDs during PS&E design review once PWD project manager confirms components are finalized.
- 3. Once received, the Design Consultant should incorporate these mark-ups into the pre-final and final plan sets.
- 4. Component IDs are typically included in a tabular format on the design sheets.



#	COMPONENT ID	COMPONENT TYPE	PIPE LENGTH (FT)
1	G14290101-14-05	GREEN HWY GRATE INLET	N/A
2	G14290101-20-05	DISTRIBUTION PIPE	75
3	G14290101-21-05	UNDERDRAIN	43
4	G14290101-50-05	CLEANOUT	N/A
5	G14290101-50-10	CLEANOUT	N/A
6	G14290101-51-05	OBSERVATION WELL	N/A
7	G14290101-60-05	HWY GRATE INLET	N/A
		•	

Figure 6 – Example Maintenance Component IDs 1 through 7 with reference table

### 3.3 Dimensions & Elevations

Comprehensive dimensioning of GSI plans is critical to achieving accurate construction and calculation of green storage metrics. Designers should ensure that sufficient dimensions are provided to determine compliance with design requirements.

- 1. All controlling and designed elevations must be dimensioned in section or profile/elevation view, as appropriate. Refer to standard callouts in *Appendix A* for more information on required elevations. To reduce the potential for inconsistency within the plan set, elevations should not be presented in plan view unless they are related to grading plans in which case grade elevations for new sidewalk and paving including direction and cross-slopes should be shown on plan view.
- 2. Lengths and widths of all proposed items must be dimensioned in plan view from a fixed reference point. The standard reference point is the Point of Intersection (PI) as the curbline is more permanent than other street features.
- 3. Distance between tree pits should be shown from center of pit to center of pit where tree will be planted.
- 4. Include dimensions of horizontal offsets from existing street features (utility poles, hydrants, laterals, buildings, fences, property line, etc.) that impact the location for proposed work.

### 3.4 Landscape Plans

- 1. Use abbreviations when labeling plants and include a translation table with additional information.
- 2. Use a simple key for abbreviations by using the first letter of the genus and the first letter of the species for each plant, capitalizing both letters. Example: A red maple tree, *Acer rubrum*, would be represented with the key "AR". If a key happens to be the same for multiple plants, use either of the following:
  - a. Add the next letter that does not conflict from the species to the end of the key (example: Acer rubrum (AR) and Agasache rupestris (ARP)), or
  - b. If there are two of the same species and one is a cultivar/variety, use the first letter of the cultivar/variety (example: *Acer rubrum* (AR) and *Acer rubrum* 'Armstrong' (ARA)).
- 3. Label trees with a Tree Location ID callout
  - a. S###-## = tree pit in trench system, VS####-## = vegetated system tree, NS###-## = non-system tree, where #### is the Project ID and ## indicates the tree location.
  - b. Tree Location ID can also be included as column in the plant schedule for clarity. See example landscape plans for further guidance.
- 4. Display plant schedule for all plants proposed with the following columns in the translation table, separated by vegetation type (i.e. trees, shrubs, grasses, herbaceous, seeding):
  - a. Hatch Pattern (if applicable)
  - b. Key
  - c. Common Name
  - d. Botanical Name
  - e. Quantity
  - f. Size
  - g. Spacing
  - h. Overhead Wires (list if overhead wires are present above the proposed trees)
  - i. Sun/Shade (list the light conditions of the area in which the plant is located, not the species light requirements).
  - j. Comments

- 5. In the comments section of the plant schedule, list critical site constraints or design considerations related to the selection of the species and/or cultivars. This information is useful to include so PWD can more easily make thoughtful substitutions to align with the original intent of the landscape design. Examples of comments include: single versus multi-stem trees, height or form characteristics specifically chosen with a certain cultivar, male or female cultivars for pollination, etc. Note: Substitutions frequently occur when certain species are unavailable at local nurseries or if seasonal planting restrictions affect the species that are specified for a project.
- 6. The size of plants listed in the plant schedule must match standards of the nursery trade. For example: Single stem B&B trees are typically sold in a range of caliper size, such as "2 2½", rather than given as an exact measurement. Refer to the Chapter 5: Landscape Design Requirements in the GSI Landscape Design Guidebook for further clarification.
- 7. If a project includes both GSI and non-GSI (non-system) plants on the landscape plan, then separate plant schedules should be created to reflect the system and non-system plants. This typically only applies to partner projects where non-GSI improvements are being made in conjunction with the PWD GSI systems.
- 8. Polygons must be used to outline massings of herbaceous plants, grass species, seed mixes, and plugs. Each polygon should have a callout with the quantity of species in the massing. Polylines next to each other should not overlap. The quantity for each species massing must correlate with its spacing noted in the planting schedule.
  - a. Example: "JE (22)" would note *Juncus effusus* (Common Rush) in a massing of twenty-two plants.
  - b. Each polygon should be filled with a unique hatch for each species and incorporated into the plant schedule for each species.
- 9. Connecting leader lines may be used to label groups of shrubs and/or trees.
- 10. Tree blocks should not be used for tree trenches in order to reduce clutter. Tree pits already indicate the tree location.
- 11. The extent of stone storage areas under plantings must be shown.
- 12. If soil depths vary throughout the system, then this should be accurately depicted in the G-series of the construction document set through plan, section, and profile/elevation views.
  - a. Example: If two feet of soil is used throughout the majority of a system, but trees are being incorporated into specific areas, then G-series sheets must clearly show that the soil depth changes from 2-feet to 3-feet beneath where the trees will be planted.
  - b. Further dimensioning and annotations may be needed to show this information accurately.
- 13. For surface features, contours should be shown on landscape plans. This helps to show the bottom of basin and ponding elevations to better evaluate the species that will be inundated during various storms.
- 14. Overhead utilities, energy dissipaters, and other pertinent design features that will be visible on the surface of a system when construction is complete should be shown on landscape plans. Adjacent structures such as buildings, walls, utility poles, and existing trees should also be shown for reference. The standard design legend can be used to identify the features to prevent cluttering the landscape plans with additional callouts.

# 4.0 CAD STANDARDS

This section presents applicable standards and guidance for the preparation of GSI contract plans, utilizing AutoCAD software. The objectives of the CAD standards are to promote uniformity in the presentation of GSI contract plans by establishing a general CAD format and outlining detailed information which is required for the preparation of complete GSI drawings. The CAD standards build upon the standards set forth in the *Water & Sewer Design Manual* and Drawings Requirements outlined in *Section 3.0* by providing standard electronic templates for baseplan and design plans, linetypes, plot styles, callouts, and a block library that adhere to these requirements.

Tips and advice are included for accessing files and working in the AutoCAD environment with the developed templates. It is understood that Computer Aided Design (CAD) users have many different drafting preferences. This is not intended to teach users how to use AutoCAD, however it has been developed to explain how the templates and supporting files are setup and advises users how to manage and use the files in an efficient manner. Ultimately, the means and methods of drafting are left to the discretion of the end user.

Furthermore, it is understood that CAD users have customized options and customized file support paths for saving files such as plot styles, linetypes, shape files, etc. Therefore, it is assumed that the end user will understand where to save the provided support files.

### 4.1 CAD Platforms to Utilize

PWD requires AutoCAD 2013 or AutoCAD Civil 3D 2013 and later to be utilized. Figures within this document and supplemental resource files have been created using AutoCAD 2018. Note that PWD recommends drafting in AutoCAD rather than AutoCAD Civil 3D when working in files for which the three-dimensional functionality of Civil 3D is not needed, as AutoCAD Civil 3D is generally slower and more taxing on the available resources of the user's computer. Refer to Section 4.4 Deliverables and Data Exchange, for more information pertaining to deliverables to the Department.

## 4.2 Templates

Templates are supplied with pre-loaded styles and layers corresponding to two stages of plan preparation: baseplan and design plan. Templates are also provided for the standard PWD title block and typical GSI index sheet. All AutoCAD drawings should be created on the appropriate template.

### 4.2.1 Title Block

Plan sheets are to be plotted with the standard title block. The overall title block consists of three files, a sheet layout containing line work and data that will remain constant on all plan sheets and two attribute blocks that must be placed on and edited for each individual plan sheet for the sheet titles and additional signature lines. PWD recommends that the sheet layout be externally referenced into paper space so that any changes made to the sheet layout will be carried out on all plan sheets. The templates are designed to accept the sheet layout and attribute block references at a base point of 0,0,0. For additional detail on setting up drawing sheets and plotting, see *Appendix E*.

### 4.2.2 Index Sheet

The index sheet template is preloaded with layers and text styles and displays all information that is required to be shown on a typical index sheet including Project Title, Location Map, signature lines, etc. Refer to *Appendix F* to see a sample index sheet.

### 4.2.3 Baseplan

The baseplan template is pre-loaded with layers, text styles, multileader styles, and dimension styles that display and identify site survey existing features. All linework should be drawn on the correct layers.

### 4.2.4 Design Plan

The design plan template is pre-loaded with layers, text styles, multileader styles, dimension styles, and table styles that associate with proposed features. All linework should be drawn on the correct layers.

### 4.3 Graphic Concepts and Standards

The objective of establishing CAD graphical standards is to ensure contract documents conform to a widely recognized format. This conformance creates consistency between PWD projects and phases executed by varied Design Consultants and aids in the construction phase as well as post-construction management, operations, and maintenance.

### 4.3.1 Working Units

The standard working units for drawing files are shown in *Table 1* below. PWD expects that drawings be set to the specified working units for deliverables to PWD or exchanged between Design Consultants in such circumstances where, for example, the baseplan is created by a different Design Consultant than the design phase plan.

Baseplan			Design Plan		
Type	Unit	Precision	Туре	Unit	Precision
Linear	Engineering	0.00	Linear	Engineering	0.00
Angular	Decimal Degrees	0.0	Angular	Decimal Degrees	0.0

Table 1 - Standard Working Units

### 4.3.2 Standard Scales

All model space geometry must be drawn to actual size (1:1 ratio) in model space. The standard scales for paper space scaling and annotation are shown in *Table 2*. These scales have been pre-loaded into the templates. Be advised that many of the annotation scales have been pre-set, thus the particular naming convention of the scales must be followed.

Scale	Use	Scale	Use
1" = 1"		1" = 50'	
1" = 1'		1" = 60'	
1/8" = 1'	Baseplan Section	1" = 100'	Project Location Map
1/4" = 1'	Baseplan or Design Section	1" = 200'	Project Location Map
1" = 10'	Plan View, Elevation View	1" = 500'	Project Location Map
1" = 20'	Location Plan, Plan View	1" = 1000'	Project Location Map
1" = 30'	Location Plan	1" = 2000'	
1" = 40'	Location Plan	1" = 5000'	

**Table 2 - Standard Scales** 

### 4.3.3 User Coordinate System (UCS)

When working on larger systems or hydraulically connected systems at street intersections, rotate the plan view of a drawing to be able to convey the design information appropriately. Rather than rotate the plan in "model-space" (which should never be done) or rotate the viewport in paper space, users should apply a user coordinate system (UCS) for displaying plans at various orientations. The use of UCS is important because the native coordinate system of the drawing(s) is maintained at all times. Furthermore, the blocks developed for this standard have been created to automatically rotate and scale based on the UCS orientation and scale. Note that since it is common to insert external references or other block references that may contain coordinate data, users should pay special attention to what UCS view they are in when inserting said references and ensure that "World" coordinate system is selected.

### 4.3.4 Annotative Text for Plan View

Annotative text will be utilized for all plan view text, dimensions, and multileaders shown at multiple scales. Annotative text will scale up or down based on the annotation scale of the drawing. Annotation scales for text to be shown at multiple scales on the plan sheets will be set to the appropriate scales for deliverables and exchanges between Design Consultants. Plans should show all text, dimensions and callouts at 1"-10' for plan view and either 1"-20' or 1"-30' for the location plan. See *Appendix C* for a reference of the required plotted text heights. It should be noted that the standard callouts for profile/elevation view are not annotative and are set to plot at the correct height when scaled at 1"-10' Horizontal Scale and 1"=5' vertical scale.

### 4.3.5 Text/Dimension/Table/Multileader Styles

Each template described in Section 4.2 above includes pre-set styles for text, dimensions, tables and multileaders. Styles for items shown in both the location plan and plan view are annotative but require that the annotation scales be defined for each object created from that style.

### 4.3.6 Blocks (Standard and Dynamic)

This standard has been created to use standard and dynamic blocks. The blocks are designed to streamline drafting and give the user options for different design scenarios. Some blocks utilize attributes to allow users to edit/add/remove text within a block without corrupting the integrity of the block as it is referenced elsewhere within the same drawing. Furthermore, the dynamic functionality of select blocks adds flexibility and intelligence to the geometry through the use of custom grips and properties.

Appendix A contains an entire visual list of standard and dynamic blocks developed for this standard. The blocks are intended to be used during the baseplan and design phases of a project. Two block libraries have been developed: one for baseplans and the other for design plans.

Rather than copy and paste blocks from one drawing to another, it is strongly encouraged to save the block libraries locally on a user's computer and reference them though AutoCAD's Design Center. Saving the block libraries to a network drive has been known to cause lag and non-responsiveness in AutoCAD. To access the design center, type "DC" in the command line and press enter. From there you can navigate to the block libraries and select the appropriate block to be inserted. *Appendix E* contains tips on how to access the blocks through the design center.

Inside of the block libraries, users will also find standardized callouts to ensure consistency in how PWD GSI is identified in baseplans and design plans. Users should cut and paste the callouts from the respective block library file. The callouts are not accessible through the Design Center. Refer to *Appendix A* for the full inventory of standardized callouts.

### 4.3.7 Plot Style, Page Setup and Plotting

The templates have been designed to be compatible with a single plot style. The templates have been preset to use the developed plot style. It is the responsibility of end users to save the provided plot style at an appropriate location on their local hard drive or network drive for AutoCAD to map it properly. Instructions for plotting can be found in *Appendix E*. The *PWD GSI CAD Standards Support File Instructions for AutoCAD* document, included with the CAD templates, has instructions for adding PWD's support files to Windows' default AutoCAD support file location.

### 4.3.8 External Referencing

This standard requires that external referencing be utilized as different project stages (baseplan and design plan) exist as separate AutoCAD drawing files. For example, external referencing allows the baseplan to be underlain in the model space of the design plan so that it may be viewed alongside the proposed design. In addition, each project should utilize external referencing for setting up drawing layouts. Layouts should be created in a separate drawing file with design stages externally referenced into the model space. These drawings should not contain any other entities in model space. Layouts should externally reference the project's title block and border. See *Appendix E* for steps to externally reference files.

### 4.4 Deliverables and Data Exchange

Any exchange of contract documents in the form of electronic data between PWD and the Design Consultant will occur via one of the options indicated below.

### 4.4.1 File Sharing

Design Consultants are to use PWD's Water Engineering External Documents (WEXD) SharePoint site as the primary method for delivering/receiving electronic files. Conventional e-mail may be used for smaller files.

### 4.4.2 Additional Required File Formats

AutoCAD files (.dwg) must be submitted so that all external references are either maintained and mapped properly or binded prior to submission to PWD. This must be accomplished through the use of the "Etransmit" command in AutoCAD. The "Etransmit" command is the required method as this allows for image and PDF references to be included, as well as plot-style settings. See *Appendix E* for instructions to "Etransmit" a project.

In addition to the AutoCAD files, the Design Consultant is required to deliver a corresponding PDF file set replicating each contract plan sheet generated for each review submission. All PDF files must be representative prints at a resolution of 300 DPI that replicates the full-size sheet of Arch E1 (30" x 42").

### 4.5 File Naming Convention and Standard Reference Files

The following file naming convention will be used for all drawing files. This includes the layout drawing, external reference drawings and external reference images. Layout drawings, the drawing that contains only layout sheets and external references, should adhere to the naming convention in *Table 3*.

Table 3 - Layout Drawing Naming Convention

PWD Contract Number	Site/Project Name	File Purpose	Extension
X - # # # # # - XXXX	_xxxxx	_Baseplan Layout _Preliminary Design Layout _Substantially Complete Design Layout _Final Design Layout _Landscape Layout _Erosion Control Layout _Title Block Layout	.dwg

External reference drawings should follow the naming convention shown in *Table 4*.

Table 4 - External Reference Drawing Naming Convention

PWD Contract Number	Site/Project Name	File Purpose*	Extension
X - # # # # # - XXXX	_xxxxx	_Baseplan XREF _Preliminary Design XREF _Substantially Complete Design XREF _Final Design XREF _Landscape XREF _Erosion Control XREF _Title Block XREF	.dwg

<sup>\*</sup>Additional "File Purpose" names are acceptable when necessary.

External reference images should follow the naming convention shown in *Table 5*.

Table 5 – External Reference Images Naming Convention

PWD Contract Number	Site/Project Name	File Purpose*	Extension
X - # # # # # - XXXX	_xxxxx	_Aerial _Map _Plan	.tiff .jpeg .dwf .pdf

<sup>\*</sup>Additional "File Purpose" names are acceptable when necessary.

# 4.6 Layer Naming Convention

The provided templates aim to provide all necessary layers, but additional layers may be required on a per project basis. When adding additional layers, care should be taken to keep layer names under 25 characters long. Abbreviations may be used where appropriate. The layer naming convention illustrated in *Table 6* provides guidance for naming additional layers when needed.

**Table 6 – Layer Naming Convention** 

GIS (Optional)*	Prefix/Discipline	Category (Optional)	Feature	Sub-Type (Optional)
GIS-	EX- G-	PROF- UTIL- TEXT-	XXXXX	-TEXT -HATCH

<sup>\*</sup>Some layers may require Geographic Information System (GIS) database exportation. The GIS- prefix allows for these layers to be queried and imported to a GIS program.

**APPENDIX A: CALLOUT AND BLOCK LIBRARY** 

### **CALLOUT VARIABLES**

The callout library was created to be applicable to numerous proposed and existing features in a green stormwater infrastructure project. This table has been created to assist the user in determining the appropriate information to complete these callouts for a specific project. Callout variables are typically enclosed within angle brackets, "<" and ">" and the contents describe the information that the user will insert. In cases where the user is expected to insert a numeric value, the letter "X" is used as a placeholder. Callouts are to be cut and paste from the block library file into design template files as needed. Callouts are not accessible through the Design Center.

Different levels of detail are displayed using callouts in the various views shown on a project plan sheet. Generally location plans show only existing feature callouts. Plan views show existing feature callouts along with proposed features callouts omitting detailed design information. Profiles and sections views include more design details for proposed features such as elevations.

Variable	Possible Values		
X,XXX	Drainage Area (SF)		
XXXX-XX	System Number		
XXXX-XX-XX	SMP Number		
+XX.XX	Elevation		
	• T-XX		
<plan sheet=""></plan>	• G-XX		
<plan sheets<="" td=""><td>• L-XX</td><td></td></plan>	• L-XX		
	<ul> <li>DA-XX</li> </ul>		
<surface type=""></surface>	<ul> <li>PERVIOUS</li> </ul>	<ul> <li>IMPERVIOUS</li> </ul>	
	BASIN	<ul> <li>INLET DISCONNECTION</li> </ul>	
	<ul> <li>BLUE ROOF</li> </ul>	<ul> <li>PERVIOUS PAVING</li> </ul>	
	<ul> <li>BUMP-OUT</li> </ul>	<ul> <li>STORMWATER PLANTER</li> </ul>	
	<ul> <li>DEPAVING</li> </ul>	RAIN GARDEN	
<smp type=""></smp>	<ul> <li>DRAINAGE WELL</li> </ul>	STORMWATER TREE	
	<ul> <li>GREEN GUTTER</li> </ul>	• SWALE	
	<ul> <li>GREEN ROOF</li> </ul>	TREE TRENCH	
	<ul> <li>INFILTRATION/STORAGE TRENCH</li> </ul>	WETLAND	
<liner></liner>	FULLY LINED	PARTIALLY LINED	
	HWY GRATE INLET	GREEN SHALLOW CITY INLET W/ APRON  OPERAL BLANK CATCULAR AND CITY (AND EXTRACT)  APPROXIMATELY	
<inlet style=""></inlet>	CITY INLET	GREEN DUAL CATCH BASIN CITY INLET W/ APRON     GREEN BUAL CATCH BASIN CITY INLET W/ APRON	
<iinlet style=""></iinlet>	OMG INLET	GREEN DUAL CATCH BASIN HWY GRATE INLET  OTHER (Overlage Inlets)	
	<ul><li>GREEN CITY INLET W/ APRON</li><li>GREEN HIGHWAY GRATE INLET</li></ul>	OTHER (Custom Inlets)	
		TO BE REMOVED	
	<ul><li>TO BE ABANDONED</li><li>TO BE PROTECTED AND SUPPORTED</li></ul>	TO BE REMOVED     TO BE REMOVED AND RESET	
<construction< td=""><td>TO BE PROTECTED     TO BE PROTECTED</td><td>TO BE REMOVED AND RESET     TO BE RESTORED</td></construction<>	TO BE PROTECTED     TO BE PROTECTED	TO BE REMOVED AND RESET     TO BE RESTORED	
NOTES>	TO BE I NOTECTED      TO BE RELOCATED	OTHER	
	RCP	• VCP	
<sewer style=""></sewer>	RCP     Brick	• TCP	
	• DI	• VCP	
<pipe material=""></pipe>	RCP	HDPE	
VI II E WATERIAL	RCEP	• PP	
	• PVC	• 11	
	Water	Verizon	
	Sewer	SEPTA	
<utility name=""></utility>	Storm Sewer	Steam	
	PECo	Sinclair Refinery Line	
	• Gas		
TOD	• TC	• RIM	
<top></top>	• GRATE		
CONNECTION		<ul> <li><inlet style=""></inlet></li> </ul>	
<connection></connection>	OTHER	-	
<underdrain></underdrain>	X/X" ORIFICE	SOLID CAP	

# **BASEPLAN BLOCK LIBRARY**

### **PLAN VIEW - EXISTING UTILITY CALLOUTS**

```
Gas X", X'-X" Cover
 Water X", X'-X" Cover
PECo X"xX" Conduit, X'-X" Cover
 Verizon X"xX", X'-X" Cover
 SEPTA X", X'-X" Cover
 Sewer X" Dia. <SEWER STYLE>, X'-X" Cover
 Sanitary Sewer X" Dia. <SEWER STYLE>, X'-X" Cover
 Storm Sewer X" Dia., X'-X" Cover
 Steam X" Dia., X'-X" Cover
 Sinclair Refinery Line X", X'-X" Cover
- Unk. Utility X", X'-X" Cover
- Gas X", X'–X" Cover (ABANDONED)
Water X", X'-X" Cover (ABANDONED)
- PECo X"xX" Conduit, X'-X" Cover (ABANDONED)
Verizon X"xX", X'-X" Cover (ABANDONED)
 SEPTA X", X'-X" Cover (ABANDONED)
 Sewer X" Dia. <SEWER STYLE>, X'-X" Cover (ABANDONED)
 Sanitary Sewer X" Dia. <SEWER STYLE>,
 X'-X" Cover (ABANDONED)
 Storm Sewer X" Dia., X'-X" Cover (ABANDONED)
 Steam X'' Dia., X'-X'' Cover (ABANDONED)
 Sinclair Refinery Line X", X'-X" Cover (ABANDONED)
Stubbed Sewer Lateral (Typ.)
```

# **BASEPLAN BLOCK LIBRARY**

### **SECTION - EXISTING UTILITY CALLOUTS**

```
-Gas X", X'—X" Cover
Water X", X'-X" Cover
PECo X"xX" Conduit, X'-X" Cover
-Verizon X"xX", X'-X" Cover
SEPTA X", X'-X" Cover
- Sewer X" Dia. <SEWER STYLE>, X'-X" Cover
·Sanitary Sewer X" Dia. <SEWER STYLE>, X'-X" Cover
-Storm Sewer X" Dia., X'—X" Cover
- Steam X'' Dia., X'-X'' Cover
Sinclair Refinery Line X", X'-X" Cover
-Unk. Utility X", X'-X" Cover
-Gas X", X'-X" Cover (ABANDONED)
-Water X", X'—X" Cover (ABANDONED)
- PECo X"xX" Conduit, X'-X" Cover (ABANDONED)
-Verizon X"xX", X'-X" Cover (ABANDONED)
SEPTA X", X'-X" Cover (ABANDONED)
Sewer X" Dia. <SEWER STYLE>, X'-X" Cover (ABANDONED)
Sanitary Sewer X" Dia. <SEWER STYLE>,
 X'-X" Cover (ABANDONED)
- Storm Sewer X" Dia., X'—X" Cover (ABANDONED)
 Steam X" Dia., X'-X'' Cover (ABANDONED)
Sinclair Refinery Line X", X'-X" Cover (ABANDONED)
```

# **BASEPLAN BLOCK LIBRARY**

### **EXISTING INLET AND MANHOLE CALLOUTS**

Manhole (No. X) Rim Elev. +XX.XX <TOP> Elev. +XX.XX Inv. Elev. +XX.XX (+XX.XX SRE) Inv. Out Elev. +XX.XX Manhole Manhole Rim Elev. +XX.XX Rim Elev. +XX.XX Inv. Elev. +XX.XX (+XX.XX SRE) Inv. Elev. +XX.XX (+XX.XX SRE) N Inv. Elev. +XX.XX (+XX.XX SRE) Inv. Elev. +XX.XX (+XX.XX SRE) S Inv. Elev. +XX.XX (+XX.XX SRE) E Inv. Elev. +XX.XX (+XX.XX SRE) W

### SURFACE TYPE CALLOUTS

C. Curb Bituminous Paving Gravel Gr. Ftw. S.R.L. S.R.E. Blue St. Curb Concrete Paving Mulch SI. Ftw. Dep. Curb Macadam Paving Asph. Ftw. Br. Gutter Gr. Curb Dirt C. Ftw. D/W Asphalt Paving Grass Br. Ftw. C. Alley

# SITE FEATURE CALLOUTS

Br. Wall C. Pad Bench St. Wall Ramp X' High < Insert Type> Fence C. Wall Window Well X' High <Insert Type> Wall Gate Vacant Lot X Story < Insert Type > Row House Parking Lot X Story < Insert Type > Building #<Insert Lot No.> TC +XX.XX BC +XX.XX TS +XX.XX BS +XX.XX /-- +XX.XX

### **PLAN VIEW - EXISTING UTILITY CALLOUTS**

```
Water X", X'-X" Cover

PECo X"xX" Conduit, X'-X" Cover

Verizon X"xX", X'-X" Cover

SEPTA X", X'-X" Cover

Sewer X" Dia. <SEWER STYLE>, X'-X" Cover

Stubbed Sewer Lateral (Typ.) (<CONSTRUCTION NOTES>)

Sanitary Sewer X" Dia. <SEWER STYLE>, X'-X" Cover

Storm Sewer X", X'-X" Cover

Steam X" Dia., X'-X" Cover


Sinclair Refinery Line X", X'-X" Cover

Unk. Utility X", X'-X" Cover


<UTILITY NAME> X", X'-X" Cover (ABANDONED)

(<CONSTRUCTION NOTES>)
```


### PLAN VIEW - EXISTING FEATURES CALLOUTS




# **PLAN VIEW - SMP CALLOUTS**




**PLAN VIEW - COMPONENT LABELING** 




### **PLAN VIEW - LANDSCAPING CALLOUTS**




### PLANVIEW - PROPOSED FEATURES CALLOUTS




### DRAINAGE AREA CALLOUT



# **PLAN VIEW - SMP PIPE CALLOUTS**



### **PLAN VIEW - DIM. STYLES**




### **PROFILE - EXISTING UTILITY CALLOUTS**

```
Gas X", X'-X" Cover
 -Water X", X'-X" Cover
 -PECo X"xX" Conduit, X'—X" Cover
 -Verizon X"xX", X'-X" Cover
 -SEPTA X", X'-X" Cover
 -Sewer X"Dia. <SEWER STYLE>, X'-X"Cover
 -Stubbed Sewer Lateral (Typ.) (<CONSTRUCTION NOTES>)
 Sanitary Sewer X'' Dia. <SEWER STYLE>, X'-X'' Cover
 -Storm Sewer X", X'—X" Cover
 -Steam X" Dia., X'-X" Cover
 -Sinclair Refinery Line X'', X'-X'' Cover
— Unk. Utility X'', X'-X'' Cover
  <UTILITY NAME> X", X'-X" Cover (ABANDONED)
  (<CONSTRUCTION NOTES>)
 -X:X Projection
 2:1 Zone of Influence
 Bearing Zone
  <uTILITY NAME> Lateral
  <utility NAME> X", X'-X" Cover
  (<CONSTRUCTION NOTES>)
```


NOTE: PROFILE CALLOUT TEXT IS SIZED AT HALF HEIGHT AND DOUBLE WIDTH IN ORDER TO DISPLAY CORRECTLY AT 1"=5' VERTICAL SCALE AND 1"=10' HORIZONTAL SCALE.

# DESIGN PLAN BLOCK LIBRARY PROFILE - EXISTING FEATURES CALLOUTS



NOTE: PROFILE CALLOUT TEXT IS SIZED AT HALF HEIGHT AND DOUBLE WIDTH IN ORDER TO DISPLAY CORRECTLY AT 1"=5" VERTICAL SCALE AND 1"=10" HORIZONTAL SCALE.


### **PROFILE - SMP CALLOUTS**



NOTE: PROFILE CALLOUT TEXT IS SIZED AT HALF HEIGHT AND DOUBLE WIDTH IN ORDER TO DISPLAY CORRECTLY AT 1"=5" VERTICAL SCALE AND 1"=10" HORIZONTAL SCALE.


\*THE DEFAULT LEADER HEAD IS THE FILLED TRIANGLE WHICH IS USED WHEN POINTING DIRECTLY AT AN OBJECT. A DOT LEADER HEAD IS USED WHEN POINTING TO THE INTERNAL AREA OF AN OBJECT. THE LEADER HEAD MAY BE CHANGED TO A MEDIUM DOT IN THE PROPERTIES UNDER LEADERS>ARROWHEAD>USER ARROW.

#### **PROFILE - SMP PIPE CALLOUTS**



NOTE: PROFILE CALLOUT TEXT IS SIZED AT HALF HEIGHT AND DOUBLE WIDTH IN ORDER TO DISPLAY CORRECTLY AT 1"=5' VERTICAL SCALE AND 1"=10' HORIZONTAL SCALE.

#### **PROFILE - DIM. STYLES**



NOTE: IN ADDITION TO 1" = 10', THE DESIGN BLOCK LIBRARY CONTAINS SCALE OPTIONS FOR 1" = 20' AND 1" = 30', WHICH CAN BE USED IN CONJUNCTION WITH PLAN VIEW SCALES OF 1" = 20' OR 1" = 30' RESPECTIVELY.

#### PROFILE - SMP INLET/SURFACE FEATURE CALLOUTS


	VII VI TRENCH RRAIN W/ ARRON
X' <inlet style=""></inlet>	X" x X' TRENCH DRAIN W/ APRON <top> ELEV. +XX.XX</top>
<top> ELEV. +XX.XX</top>	,
GUTTER ELEV. +XX.XX	GUTTER ELEV. +XX.XX
X" OUT INV. ELEV. +XX.XX	X" OUT INV. ELEV. +XX.XX
TO <connection></connection>	TO <connection></connection>
/— X' <inlet style=""></inlet>	SW MANHOLE
<top> ELEV. +XX.XX</top>	/ RIM ELEV. +XX.XX
GUTTER ELEV. +XX.XX	X" IN INV. ELEV. +XX.XX
<b>1</b> /	FROM <connection></connection>
X" IN INV. ELEV. +XX.XX	X" OUT INV. ELEV. +XX.XX
FROM <connection></connection>	TO <connection></connection>
X" OUT INV. ELEV. +XX.XX	— X'xX' JUNCTION BOX
TO <connection></connection>	RIM ELEV. +XX.XX
V' ZINII ET CTVI ES	X" IN INV. ELEV. +XX.XX
X' <inlet style=""></inlet>	FROM <connection></connection>
<top> ELEV. +XX.XX</top>	X" OUT INV. ELEV. +XX.XX
GUTTER ELEV. +XX.XX	TO <connection></connection>
X" IN INV. ELEV. +XX.XX	
CORED INTO INLET WITH	WATER LEVEL CONTROL STRUCTURE
<underdrain></underdrain>	RIM ELEV. +XX.XX
FROM <connection></connection>	WEIR ELEV. +XX.XX
15" OUT INV. ELEV. +XX.XX	3" PVC CENTERLINE ELEV. +XX.XX
TO SEWER	WITH <underdrain></underdrain>
∕— X'xX' OVERFLOW	X" IN INV. ELEV. +XX.XX
CONTROL STRUCTURE	FROM <connection></connection>
<top> ELEV. +XX.XX</top>	X" OUT INV. ELEV. +XX.XX
X" IN INV. ELEV. +XX.XX	TO <connection></connection>
CORED INTO STRUCTURE	/— HEADWALL
WITH <underdrain></underdrain>	/ TW ELEV. +XX.XX
FROM <connection></connection>	X" IN INV. ELEV. +XX.XX
X" OUT INV. ELEV. +XX.XX	FROM <connection></connection>
TO <connection></connection>	/— <inlet style=""></inlet>
	<top> ELEV. +XX.XX</top>
XX" DOMED RISER	GUTTER ELEV. +XX.XX
RIM ELEV. +XX.XX	WEIR ELEV. +XX.XX
X" OUT INV. ELEV. +XX.XX	X" IN INV. ELEV. +XX.XX
TO <connection></connection>	FROM <connection></connection>
/ XX" DOMED RISER W/ SUMP	X" IN INV. ELEV. +XX.XX
RIM ELEV. +XX.XX	CORED INTO INLET WITH <underdrain></underdrain>
X" OUT INV. ELEV. +XX.XX	FROM <connection></connection>
TO <connection></connection>	X" OUT INV. ELEV. +XX.XX
10 COMMEDITORS	TO <connection></connection>
/ XX" DOMED RISER STANDPIPE	15" OUT INV. ELEV. +XX.XX
/ RIM ELEV. +XX.XX	TO SEWER

NOTE: PROFILE CALLOUT TEXT IS SIZED AT HALF HEIGHT AND DOUBLE WIDTH IN ORDER TO DISPLAY CORRECTLY AT 1"=5" VERTICAL SCALE AND 1"=10" HORIZONTAL SCALE.

#### **SECTION - EXISTING UTILITY AND FEATURE CALLOUTS**




#### **SECTION - SMP CALLOUTS**




NOTE: THE DEFAULT LEADER HEAD IS THE FILLED TRIANGLE WHICH IS USED WHEN POINTING DIRECTLY AT AN OBJECT. A DOT LEADER HEAD IS USED WHEN POINTING TO THE INTERNAL AREA OF AN OBJECT. THE LEADER HEAD MAY BE CHANGED TO A MEDIUM DOT IN THE PROPERTIES UNDER LEADERS>ARROWHEAD>USER ARROW.


#### **SECTION - SMP PIPE CALLOUTS**



#### SECTION - SMP INLET/SURFACE FEATURE CALLOUTS



#### **SECTION - DIM. STYLES**



NOTE: IN ADDITION TO 1/4" = 1', THE DESIGN BLOCK LIBRARY CONTAINS SCALE OPTIONS FOR 1/8" = 1', AND 1/12" = 1', WHICH CAN BE USED IN CONJUNCTION WITH PLAN VIEW SCALES OF 1" = 20' OR 1" = 30', RESPECTIVELY.

# **EXAMPLE COMPONENT ID TABLE**

#	COMPONENT ID	COMPONENT TYPE	PIPE LENGTH (FT)
1		GREEN CITY INLET W/ APRON	N/A
2		GREEN SHALLOW CITY INLET W/ APRON	N/A
3		GREEN HWY GRATE INLET	N/A
4		GREEN DUAL CATCH BASIN CITY INLET W/ APRON	N/A
5		GREEN DUAL CATCH BASIN HWY GRATE INLET	N/A
6		GREEN DUAL CATCH BASIN OMG INLET	N/A
7		DISTRIBUTION PIPE	XX
8		UNDERDRAIN	XX
9		XX'' x XX' TRENCH DRAIN W/ APRON	N/A
10		CONCRETE HEADWALL W/ ENERGY DISSIPATER	N/A
11		CLEANOUT	N/A
12		OBSERVATION WELL	N/A
13		SW MANHOLE	N/A
14		SW JUNCTION MANHOLE	N/A
15		DOMED RISER	N/A
16		INFILTRATION COLUMN	N/A
17		DOMED RISER STANDPIPE	N/A
18		HWY GRATE INLET	N/A
19		CITY INLET	N/A
20		OMG INLET	N/A
21		WATER LEVEL CONTROL STRUCTURE	N/A
22		2'x2' OVERFLOW CONTROL STRUCTURE	N/A
23		2'x4' OVERFLOW CONTROL STRUCTURE	N/A
24		2'x2' JUNCTION BOX	N/A
25		2'x4' JUNCTION BOX	N/A

# **EXISTING FEATURE LABELS**

VENT BOX-SEWER*	GAS BOX*	WATER BOX*	UNKNOWN CURB BOX*	
□v	□¢	□w	□?	
POLE*	BENCHMARK*	LAMP POST*	IRON POST*	
<b>○</b> P#	<b>⊞</b> вм	OLP	QIР	
BOLLARD*	PARKING METER*	PE POLE	TRASH RECEPTACLE*	
OB	⊗PM	<del></del>	Trash	
PE POLE W/ LIGHT	SEPTA POLE*	TRAFFIC SIGN*	TRAFFIC LIGHT*	
# <b>\( \rightarrow </b>	○SP#	ots o <i>ts(20')</i>	Oπ	
HEDGE	BENCH*	TREE CANOPY	TREE STUMP	
	Bench	+ xx"	<b>#</b> "	
FIRE HYDRANT*	FIRE ALARM BOX*	SEPTA BUS SHELTER* Bus Shelter	*DO NOT MANUALL ROTATE BLOCKS CONTAINING NON-ATTRIBUTE TE WILL ROTATE AUTOMATICALLY T UPRIGHT IN ALL UC IN THE LAYOUT VIE BLOCKS WITH TEXT	EXT. TEXT O REMAIN S VIEWS WPORT.
			ROTATED WITH DYI BLOCK GRIP. SEE A E OF THE PWD GSI AND DRAWING STA FOR INSERTION INSTRUCTIONS.	NAMIC APPENDIX SURVEY

#### **EXISTING FEATURE LABELS CONT.**

	·	·	·	
STANDPIPE*	ELECTROLYSIS TEST STATION*	DOOR SILL*	CURB RAMP*	COMPLIANT CURB RAMP
\$	T	<u>Door</u>		C/R
COAL CHUTE*	WINDOW GRATE	DOWNSPOUT*	MAIL BOX*	
<b>○cc</b>		<b>○</b> DS	∏МВ	
CABLE TV ACCESS BOX*	TRAFFIC SIGNAL CONTROLLER*	PAY PHONE*	PORCH	
				*DO NOT MANUALLY
CATV	Traffic Control	P <u>hon</u> e		*DO NOT MANUALLY ROTATE BLOCKS CONTAINING
				NON-ATTRIBUTE TEXT. TEXT WILL
STEAM GRATE*	SEWER MANHOLE	MANHOLE	MANHOLE UNKNOWN*	ROTATE AUTOMATICALLY TO REMAIN
CDATE.				UPRIGHT IN ALL UCS VIEWS IN THE
GRATE	<u></u> #	O	?	LAYOUT VIEWPORT. BLOCKS WITH TEXT MAY BE ROTATED
WATER (OAC MALVE	O.T.C.D.C.		CUDVEY CTONE*	WITH DYNAMIC BLOCK GRIP. SEE
WATER/GAS VALVE	STEPS	CELLAR DOOR	SURVEY STONE*	APPENDIX E OF THE PWD GSI SURVEY AND DRAWING
				STANDARDS FOR INSERTION
			_]ss	INSTRUCTIONS.
				l

# **EXISTING MISC. LABELS**

A1 <b>◄</b>	BORING	CURB FLOW ARROW	EXISTING CONTOUR LABEL	CENTERLINE ELEVATIONS
SECTION ARROW	<b>*</b>	<b>Y</b>	- 0.00	<u>CL</u>  +##-##
SECTION TITLE	NORTH ARROW	TOP/BOTTOM OF	TOP/BOTTOM OF	EXISTING SPOT
		CURB CALLOUT	STEP CALLOUT	ELE VA TION
<u>S E C T I O N A — A</u> SCALE: 1/4" = 1'-0"		TC +XX.XX BC +XX.XX	TS +XX.XX BS +XX.XX	+XX.XX

#### STREET CALLOUTS

	OTIVEET	ALLUUIS	
TWO—WAY W/PARKING	TWO—WAY W/ NO PARKING	TWO—WAY W/PARKING ONE SIDE	TWO-WAY STATE ROUTE CUSTOM
STREET  PARKING	STREET	STREET  PARKING	STREET (S.R. XXXX)
PARKING	$\Diamond$		
TWO-WAY W/ 4 CUSTOM LINES AND MULTIPLE ARROW OPTIONS	TWO-WAY W/ 4 CUSTOM LINES	ONE-WAY W/ PARKING	ONE-WAY STATE ROUTE CUSTOM
STREET	STREET	STREET	STREET
  	 ▷	PARKING PARKING	(S.R. XXXX)
ONE-WAY W/ NO PARKING	ONE—WAY W/ PARKING ONE SIDE	ONE-WAY W/ 4 CUSTOM LINES	ONE-WAY W/ 4 CUSTOM LINES AND MULTIPLE ARROW OPTIONS
STREET	STREET	STREET	STREET
<b>──</b>	PARKING⊳		————

NOTE: BIKE LANES SHOULD BE ADDED TO STREET CALLOUTS AS NECESSARY

CITY, HWY, OMG, GRATE INLETS

4' CITY  4CI	4' HIGHWAY GRATE 4	4' OMG 4
6' CITY 6CI	6' HIGHWAY GRATE 6	6' OMG 6
#1 CITY	#2 CITY	#3 CITY  #3
#4 CITY	#1 GRATE	#2 GRATE  #2 #2
#3 GRATE	#4 GRATE	

#### **DESIGN PLAN BLOCK LIBRARY SECTION VIEW INLETS** GREEN DUAL GREEN DUAL **GREEN GREEN HIGHWAY CITY OMG** GREEN CATCH BASIN CATCH BASIN **GRATE** SHALLOW **HIGHWAY CITY** CITY **HWY** CITY **GRATE PROFILE VIEW INLETS HIGHWAY** GREEN **GREEN** GREEN GREEN DUAL GREEN DUAL CITY OMG **SHALLOW** CATCH BASIN CATCH BASIN **GRATE HIGHWAY** CITY CITY **HWY GRATE** CITY **PLAN VIEW INLETS** 4' GREEN CITY OR **6' HWY** 4' HWY 4' CITY 4' GREEN 4' GREEN GRATE **HWY GRATE GRATE SHALLOW CITY** 6' CITY 4' OMG **GREEN DUAL** 6' OMG **GREEN DUAL CATCH BASIN CATCH BASIN HWY CITY** ADDITIONAL PROPOSED STRUCTURES PROPOSED MANHOLE 2'X2' OVERFLOW 2'X4' OVERFLOW CONTROL STRUCTURE CONTROL STRUCTURE **PROFILE PLAN PLAN** PLAN **PROFILE SECTION PROFILE SECTION SECTION** 2'X4' JUNCTION BOX **WATER LEVEL** 2'X2' JUNCTION BOX CONTROL STRUCTURE **PLAN PLAN** PLAN **PROFILE** PROFILE SECTION **PROFILE** SECTION SECTION

# **SEWER SECTION**

EGG SHAPED	EGG SHAPED	EGG SHAPED	EGG SHAPED
2'-3" X 1'-6"	2'-6" X 1'-8"	3'-0" X 2'-0"	3'-3" X 2'-2"
EGG SHAPED	EGG SHAPED	EGG SHAPED	EGG SHAPED
3'-6" X 2'-4"	4'-0" X 2'-8"	4'-6" X 3'-0"	5'-0" X 3'-4"
CIRCULAR	CIRCULAR	CIRCULAR	CIRCULAR
2'-0" DIA.	2'-3" DIA.	2'-6" DIA.	2'-9" DIA.
CIRCULAR	CIRCULAR	CIRCULAR	CIRCULAR
3'-0" DIA.	3'-6" DIA.	4'-0" DIA.	4'-3" DIA.
CIRCULAR	CIRCULAR	CIRCULAR	VCP
4'-6" DIA.	4'-9" DIA.	5'-0" DIA.	10" DIA.
			<u>o</u>

#### **SEWER SECTION CONT.**

VCP 12" DIA.	VCP 15" DIA.	VC 18" I		VCP 21" DIA.	VCP 24" DIA.
O	<b>Q</b>	C			
VCP 27" DIA.	VCP 30" DIA.	36" I		VCP 42" DIA.	RCP 15" DIA.
					<u>O</u>
RCP 18" DIA.	RCP 21" DI			RCP " DIA.	RCP 27" DIA.
			]		
RCP 30" DIA.	RCP 36" DI			RCP " DIA.	RCP 48" DIA.
		)			
RCP 54" DIA.	RCP 60" DI			RCP 5" DIA.	RCP 72" DIA.

#### **LABELS**

**PROPOSED** SYSTEM NUMBER **MATCHLINE CONTOUR LABEL PLAN VIEW** MATCHLINE -0.00 **SYSTEM XXXX-X** SEE SHEET G-# SECTION/DETAIL TITLE **INLET LABEL** A1-**PLAN VIEW** SECTION A1-A1 SCALE: 1/4" = 1'-0" (G) (R) **SECTION ARROW DETAIL NAME (4) (6)** SCALE: N.T.S.

#### **PROFILE TITLE**

# SYSTEM XXXX-XX

#### **ELEVATION VIEW**

HORIZONTAL SCALE: 1" = 10'-0" VERTICAL SCALE: 1" = 5'-0"

#### ALTERNATIVE PROFILE TITLE

#### **ELEVATION VIEW A1-A1**

HORIZONTAL SCALE: 1" = 10'-0" VERTICAL SCALE: 1" = 5'-0"

#### **CROSS STREET SECTION TITLE**

CROSSING ##TH ST. TO CROSS-STREET INLET ( SECTION A1 - A1 )

SCALE: 1/4" = 1'-0"

# DESIGN PLAN NOTE FOR WORK NEAR OVERHEAD WIRES

NOTE: OVERHEAD WIRES ON X SIDE OF X STREET.


# DESIGN PLAN NOTE FOR WORK NEAR TRANSMISSION MAINS

NOTE: THE CONTRACTOR IS ADVISED TO DEPROSE CAUTION DAMNG CONSTRUCTION ABOVE, BELOW, OR ADMICIST TO THE XX\* WATER MAIN SUFFICIENT CLASSINGE SHOULD BE MAINTAINED SETTINED ANY PROPOSED FIVES AND HE DISTRICT MAIN AT CRESSINGE, I POD MORPHOLITOR FOR THE ADMIT CHARLES AND ADMIT CHARLES AND THE CONTRACT OF THE ADMIT CHARLES AND THE CHARLES


**SMP FEATURES** 

		MIP FEATURES	<u> </u>	
CLEANOUT  PLAN PROFILE	12" DOMED RISER STANDPIPE  PLAN PROFILE	OBSERVATION WELL O PLAN PROFILE	INFILTRATION COLUMN	PIPE FITTINGS PROFILE VERTICAL BENDS D HORIZONTAL BENDS
12" DOMED	12" DOMED	TRAP PROFILE	TRAP SECTION	ON CO
RISER  PLAN PROFILE	RISER W/ SUMP  PLAN PROFILE		†ì	DOUBLE HORIZONTAL BENDS \$\text{\$1}\$ 8"X12" PIPE REDUCER
SEWER CONNECTIONS	ANTI SEEP COLLAR	TRENCH DRAIN	CONCRETE APRON	CONCRETE APRON AT
RECONNECT	I PLAN			BUMPOUT
I NEW CONNECTION	PROFILE			
WYE FITTING	FLEXIBLE COUPLING	SEWER VENT	UTILITY SLEEVE	PROPOSED ENDWALL
		_ □ν	<b>I</b>	/ PLAN
<del>I⊠I</del> PLAN	PLAN	₽LAN		PROFILE
PROFILE	PROFILE	PROFILE		SECTION


#### **ENERGY DISSIPATERS**




#### **EROSION & SEDIMENTATION CONTROL**



# DESIGN PLAN BLOCK LIBRARY SIGN, POLE, LIGHT




#### **STREET FEATURES**




\*DO NOT MANUALLY ROTATE BLOCKS CONTAINING NON-ATTRIBUTE TEXT. TEXT WILL ROTATE AUTOMATICALLY TO REMAIN UPRIGHT IN ALL UCS VIEWS IN THE LAYOUT VIEWPORT. BLOCKS WITH TEXT MAY BE ROTATED WITH DYNAMIC BLOCK GRIP. SEE APPENDIX E OF THE PWD GSI SURVEY AND DRAWING STANDARDS FOR INSERTION INSTRUCTIONS.


#### PROPOSED LANDSCAPING



#### **TREE PIT**



#### TREE PIT PLAN VIEW



# **PROFILE GRID**

10 LINES	9 LINES	8 LINES	7 LINES
45 ——— 45			
40 ———40	40 ———40		
35 — 35	35 — 35	35 — 35	
30 ———30	30 ———30	30 ———30	30 ———30
25 ————————————————————————————————————	25 ————————————————————————————————————	25 ————————————————————————————————————	25 ————————————————————————————————————
20 ————20	2020	20 ————20	2020
1515	1515	1515	1515
1010	1010	1010	1010
05 ———— 05	0505	0505	05 — 05
00	00	00	00
6 LINES	5 LINES	4 LINES	3 LINES
25 ————————————————————————————————————			
20 ————20	20 ————20		
15 ————————————————————————————————————	15 ————————————————————————————————————	15 ————————————————————————————————————	
1010	1010	1010	1010
05 ————05	05 ————05	05 ————05	05 ————05
00 ———00	00 — 00	00	00

# **APPENDIX B: LINETYPES AND HATCHING**

EXISTING LINETYPES AND HATCHING							
		LOCATION / PLAN VIEW					
ITEM	STYLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE			
ROW LINE	16	CONTINUOUS LINE	1.0	N/A			
EXISTING CURB LINE	15	CONTINUOUS LINE	1.0	N/A			
PECo LINE	9	PECo LINE*	1.0	N/A			
GAS LINE	9	GAS LINE*	1.0	N/A			
VERIZON LINE	8	VERIZON LINE*	1.0	N/A			
SEPTA LINE	9	SEPTA LINE*	1.0	N/A			
SEWER LINE	9	SEWER LINE*	1.0	N/A			
WATER LINE	9	WATER LINE*	1.0	N/A			
SEPARATE SEWER LINE	9, 9	SEWER LINE* AND SANITARY SEWER LINE	1.0	N/A			
STORM SEWER LINE	9	SEWER LINE*	1.0	N/A			
STEAM	9	STEAM*	1.0	N/A			
SHRUB LINE	3	SHRUBLINE	1.0	N/A			
PROPERTY BOUNDARY	8	PROPERTY BOUNDARY*	1.0	N/A			
CROSSWALK/ STOP BAR	34	CONTINUOUS LINE	1.0	N/A			
NO PARKING BOX	34	CONTINUOUS LINE	1.0	N/A			
BUILDING LINE	5	BUILDING LINE	1.0	N/A			
			\ \	\ \			
BUILDING OUTCROP LINE	3	CONTINUOUS LINE	1.0	N/A			
FENCE	3	FENCELINEX	1.0	N/A			
EASEMENT	- X X-	EASEMENT*	1.0	N/A			

_		G LINET CHING (			
		LOCATION	/ PLAN \	/IEW	
ITEM	STYLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE	
RAILROAD	26	RAILROAD*	1.0	N/A	
GRASS	32	GRASS	3.5	VARIES	
ψ ψ	$\forall$	Ψ Ψ	$\forall$	<b>V</b>	
GSI SYSTEM	3	CONTINUOUS LINE	1.0	N/A	
OVERHEAD WIRE	9	онw	1.0	N/A	
OHW	OHW —	OHW O	 HW	онw <b>—</b>	

\*USER DEFINED LINETYPE.
NOTES: ALL HATCHES IN LOCATION/
PLAN VIEW SHOULD BE
ANNOTATIVE. SET DISPLAY ORDER
FOR ALL HATCHING TO THE BACK.

TOPO\*

торо

3

ABA	_	NED U		Υ							
LOCATION / PLAN VIEW											
ITEM	STYLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE							
PECo LINE	30	PECo LINE*	1.0	N/A							
GAS LINE	30	GAS LINE*	1.0	N/A							
VERIZON LINE	30	VERIZON LINE*	1.0	N/A							
SEPTA LINE	30	SEPTA LINE*	1.0	N/A							
SEWER LINE	30	SEWER LINE*	1.0	N/A							
WATER LINE	30	WATER LINE*	1.0	N/A							
SEPARATE SEWER LINE	30,30	SEWER LINE* AND SANITARY SEWER LINE	1.0	N/A							
STORM SEWER LINE	30	SEWER LINE*	1.0	N/A							


PF	ROP	OSED LINE	ΓΥΡΕ	ES A	ND F	IAT(	CHIN	IG		
		LOCATION / PL	AN VIEW	ı	PROFILE	VIEW (1	" = 10')	SECTION VIEW (4" = 1')		
ITEM	STYLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE	LINE/ HATCH TYPE	SCALE	HATCH
PROPOSED CURB LINE	14	CONTINUOUS	1.0	N/A	CONT.	1.0	N/A	CONT.	1.0	N/A
STONE TRENCH OUTLINE W/ GEOTEXTILE ON SIDES	20	HIDDEN 2	1.0	N/A	N/A	N/A	N/A	HIDDEN2	1.0	N/A
STONE TRENCH OUTLINE W/ GEOMEMBRANE LINER ON SIDES	20	CONTINUOUS	1.0	N/A	N/A	N/A	N/A	CONT.	1.0	N/A
TRENCH HATCH BOUNDARY	18	SEE ABOVE	N/A	N/A	CONT.	1.0	N/A	N/A	N/A	N/A
TRENCH HATCH	8	DOTS	0.75	N/A	GRAVEL STYLE 34	2.0	15°	GRAVEL STYLE 34	1.0	0°
GEOMEMBRANE LINER ON BOTTOM	27	PLAST, TRANSPARENCY = 50%	1.0	45°	N/A	N/A	N/A	CONT. STYLE 20	1.0	N/A
STONE TRENCH TIER**	15	GW = 0.3	0.5	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SOLID PIPE (<24")	15	CONTINUOUS	1.0	N/A	CONT.	1.0	N/A	CONT.	1.0	N/A
SOLID PIPE (>24")	15	-	1.0	N/A	CONT.	1.0	N/A	CONT.	1.0	N/A
PERFORATED PIPE	15	PERFORATED PIPE*	1.0	N/A	DASHED	1.0	N/A	DASHED	1.0	N/A
STORMWATER SOIL	34	N/A	N/A	N/A	SOLID	40% TRANSPARENCY	0°	SOLID	40% TRANSPARENCY	0°
SAND HATCH	11	N/A	N/A	N/A	AR-SAND	0.25	0°	AR-SAND	0.25	0°
CONCRETE HATCH	34	N/A	N/A	N/A	AR-CONC	0.15	0°	AR-CONC	0.15	0°
ASPHALT HATCH	34	N/A	N/A	N/A	ANSI35	1.00	0°	ANSI35	1.00	0°
BEARING ZONE OR ZONE OF INFLUENCE	3	N/A	N/A	N/A	DASHED2	1.0	N/A	DASHED2	1.0	N/A
TURF GRASS	8	GRASS	0.15	VARIES	GRASS	1.0	N/A	GRASS	1.0	N/A
SMP PLANTING	8	CROSS + + + + + - + + + +	0.5	VARIES	N/A	N/A	N/A	N/A	N/A	N/A
PROPOSED PAVEMENT	1	AR-CONC	0.5	0°	N/A	N/A	N/A	N/A	N/A	N/A
PAVEMENT RESTORATION	1	DASHED2	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A
PERVIOUS PAVERS/ ASPHALT	14	TRIANGLE	5.0	0°	N/A	N/A	N/A	N/A	N/A	N/A
PROPOSED PAVEMENT MARKINGS	27	CONTINUOUS LINE, TRANSPARENCY = 50%, CROSSWALK/STOP BAR - GW = 2.0  NO PARKING BOX - GW = 0.33	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A
PROPOSED ROADWAY REGRADE	8	ROADWAY REGRADE	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A
PROPOSED FENCE	10	FENCELINEX X X	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DWY REPLACE OUTLINE	8	CONTINUOUS	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DRIVEWAY REPLACE HATCH	34	SOLID, TRANSPARENCY = 50%	1.0	0°	N/A	N/A	N/A	N/A	N/A	N/A
DRAINAGE AREA OUTLINE	21	DA*	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A

PR	PROPOSED LINETYPES AND HATCHING (CONT.)												
		LOCATION / PL	PROFILE	E VIEW (1	I" = 10')	SECTION VIEW (1/4" = 1')							
ITEM	STYLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE	LINE/ HATCH TYPE	SCALE	HATCH ANGLE			
LIMIT OF DISTURBANCE	21	LOD*	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
SILT FENCE	8	SF* SF SF	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
LOD/SILT FENCE	21	LOD SF*	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
SAWCUT LINE	14	DIVIDE2	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
DEMOLITION LINE	20	DEMOLITION*  *XXXXXXXXXXXXXXX	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
TREE PROTECTION ZONE	12	* <b>TPZ</b> TPZ	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
PROHIBITIVE ROOT ZONE	31	CONTINUOUS	1.0	N/A	N/A	N/A	N/A	N/A	N/A	N/A			
WOODCHIP/ PLYWOOD	8	GOST_WOOD	0.03	45°	N/A	N/A	N/A	N/A	N/A	N/A			
BACKFILL SOIL	34	N/A	N/A	N/A	EARTH	5.0	45°	EARTH	5.0	45°			
BUILDING & EXPECTED FOUNDATION	5	N/A	N/A	N/A		0.3	N/A		0.3	N/A			

#### \*USER DEFINED LINETYPE.

\*\*USE STONE TRENCH TIER LINETYPE TO IDENTIFY LOCATIONS WHERE BOTTOM OF STONE ELEVATION CHANGES, EXCEPT IN LOCATIONS WHERE CHANGE IS FOR STONE BEDDING BENEATH A SUMPED PIPE. NOTES: ALL HATCHES IN LOCATION/PLAN VIEW SHOULD BE ANNOTATIVE. SET DISPLAY ORDER FOR ALL HATCHING TO THE BACK. THE TABLES IN THIS APPENDIX DO NOT SHOW THE LINETYPES AND COLORS ASSOCIATED WITH ALL LAYERS. EXAMPLES OF ALL LAYERS CAN BE FOUND IN THE PWD GSI BASE PLAN BLOCK LIBRARY 2021 AND THE PWD GSI DESIGN PLAN BLOCK LIBRARY 2021. ACCURATE LAYER SELECTION WILL ENSURE THAT THE PROPER LINETYPE AND COLOR ARE USED WITHOUT ANY ADDITIONAL USER ACTION.

# APPENDIX C: LETTERING STANDARDS AND TEXT, MULTILEADER, DIMENSION AND TABLE STYLES



	BASE PL	AN TEXT ST	YLES - NON-AN	INOTATIVE
NAME	FONT	TEXT HEIGHT	EFFECTS	USE
EX-40	simplex.shx	0.40	Width Factor: 1.0 Oblique Angle: 15°	Section text
EX-100	simplex.shx	1.00	Width Factor: 1.0 Oblique Angle: 15°	Building number text
Simplex Ob	simplex.shx	0	Width Factor: 1.0 Oblique Angle: 15°	Text within block library blocks
ARIAL	Arial	0	Width Factor: 1.0 Oblique Angle: 0°	Text within block library blocks
ARIAL BOLD	Arial (Bold)	0	Width Factor: 1.0 Oblique Angle: 0°	Text within block library blocks
LINETYPES	Arial	0	Width Factor: 1.0 Oblique Angle: 0°	Linetype text
LINETYPES I	Arial (Italic)	0	Width Factor: 1.0 Oblique Angle: 0°	Linetype text
LEGEND	Calibri	0	Width Factor: 1.0 Oblique Angle: 0°	Legend text
	BASE	<b>PLAN TEXT</b>	STYLES - ANNO	DTATIVE
NAME	FONT	PAPER TEXT HEIGHT	EFFECTS	USE
EX-100a	simplex.shx	0.10	Width Factor: 1.0 Oblique Angle: 15°	Building number text
EX-60	simplex.shx	0.06	Width Factor: 1.0 Oblique Angle: 15°	Utility feature text (IE: vent box)
EX-80	simplex.shx	0.08	Width Factor: 1.0 Oblique Angle: 15°	Surface/Land use text (IE: Open Lot)

	BASE PLAN MULTILEADER STYLES												
NAME	NAME ARROWHEAD LEADER BREAK LANDING DISTANCE ANNOTATIVE MULTILEADER TYPE SOURCE BLOCK / TEXT STYLE												
EX-TXT-MISC LBL	0.10	0.1250	0.10	YES	Mtext	EX-100a	Middle of top line						
EX-TXT-SECT LBL	0.40	0.1250	0.50	NO	Mtext	EX-40	Middle of top line						
EX-TXT-ST FTR LBL	0.08	0.1250	0.08	YES	Mtext	EX-80	Middle of top line						
EX-TXT-UTL LBL	0.10	0.1250	0.10	YES	Mtext	EX-100a	Middle of top line						
EX-TC BC SPOT ELEV	0.00	0.1250	0.06	YES	Mtext	EX-60	Underline top line						
EX-TC BC SPOT ELEV	0.01	0.1250	0.06	YES	Mtext	EX-60	Middle of top line						

	BASE PLAN DIMENSION STYLES											
NAME ANNOTATIVE ARROW SIZE TEXT LINEAR UNIT FORMAT PRECISION SCALE FACTOR FORMAT DECIMAL ZERO SUPPRESSION										USE		
EX-DIMS-SECT	NO	0.56	EX-40	Architectural	0'-0"	12	Decimal Degrees	0	0 feet, 0 inches	Section dimension		
EX-DIMS-UTIL	YES	0.14	EX-100a	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Utility offset dimension		

NAME	DESIGN I	PLAN TEXT ST	YLES - NON-AN	INOTATIVE USE
FV 40	simple shy	0.40	Width Factor: 1.0	Existing soction tout
EX-40	simplex.shx	0.40	Oblique Angle: 15°	Existing section text
EX-50-HORIZ	simplex.shx	0.5	Width Factor: 2.0 Oblique Angle: 15°	Horizontal text for dimensions in elevation view at 1" = 10' scale
EX-50-HORIZ-20	simplex.shx	0.5	Width Factor: 4.0 Oblique Angle: 15°	Horizontal text for dimensions in elevation view at 1" = 20' scale
EX-50-HORIZ-30	simplex.shx	0.5	Width Factor: 6.0 Oblique Angle: 15°	Horizontal text for dimensions in elevation view at 1" = 30' scale
EX-50-VERT	simplex.shx	1.0	Width Factor: 0.5 Oblique Angle: 15°	Vertical text for dimensions in elevation view at 1" = 10' scale
EX-50-VERT-20	simplex.shx	2.0	Width Factor: 0.25 Oblique Angle: 15°	Vertical text for dimensions in elevation view at 1" = 20' scale
EX-50-VERT-30	simplex.shx	3.0	Width Factor: 0.167 Oblique Angle: 15°	Vertical text for dimensions in elevation view at 1" = 30' scale
EX-100	simplex.shx	1.00	Width Factor: 1.0 Oblique Angle: 15°	Existing plan view text
EX-120	simplex.shx	1.20	Width Factor: 1.0 Oblique Angle: 15°	Text for dimensions in section view at 1/12" = 1' scale
G-40	Arial (Bold)	0.40	Width Factor: 1.0 Oblique Angle: 0°	Proposed section text
G-50-HORIZ	Arial (Bold)	0.5	Width Factor: 2.0 Oblique Angle: 0°	Horizontal text for dimensions in elevation view at 1"=10' scale
G-50-HORIZ-20	Arial (Bold)	0.5	Width Factor: 4.0 Oblique Angle: 0°	Horizontal text for dimensions in elevation view at 1"=20' scale
G-50-HORIZ-30	Arial (Bold)	0.5	Width Factor: 6.0 Oblique Angle: 0°	Horizontal text for dimensions in elevation view at 1"=30' scale
G-50-VERT	Arial (Bold)	.95	Width Factor: 0.55 Oblique Angle: 0°	Vertical text for dimensions in elevation view at 1"=10' scale
G-50-VERT-20	Arial (Bold)	2.0	Width Factor: 0.25 Oblique Angle: 0°	Vertical text for dimensions in elevation view at 1"=20' scale
G-50-VERT-30	Arial (Bold)	3.0	Width Factor: 0.167 Oblique Angle: 0°	Vertical text for dimensions in elevation view at 1"=30' scale
G-80	Arial (Bold)	0.8	Width Factor: 1.0 Oblique Angle: 0°	Text for dimensions in section view at 1/8" = 1' scale
G-120	Arial (Bold)	1.2	Width Factor: 1.0 Oblique Angle: 0°	Text for dimensions in section view at 1/12" = 1' scale
Simplex Ob	simplex.shx	0	Width Factor: 1.0 Oblique Angle: 15°	Text within block library blocks
ARIAL	Arial	0	Width Factor: 1.0 Oblique Angle: 0°	Text within block library blocks
ARIAL BOLD	Arial (Bold)	0	Width Factor: 1.0 Oblique Angle: 0°	Text within block library blocks
LINETYPES	Arial	0	Width Factor: 1.0 Oblique Angle: 0°	Linetype text
LINETYPES I	Arial (Italic)	0	Width Factor: 1.0 Oblique Angle: 0°	Linetype text
	DESIG		STYLES - ANNO	DTATIVE
NAME	FONT	PAPER TEXT HEIGHT	EFFECTS	USE
EX-100a	simplex.shx	0.10	Width Factor: 1.0 Oblique Angle: 15°	Existing plan view text
G-100	Arial (Bold)	0.10	Width Factor: 1.0 Oblique Angle: 0°	Proposed plan view text
G-100	Arial (Bold)	0.10	Width Factor: 1.0 Oblique Angle: 0°	Proposed landscape plan view text
Note: The 1'	'' = 20' an	d 1'' = 30' sca	les are intende	d for use with profiles

Note: The 1" = 20', and 1" = 30' scales are intended for use with profiles that correlate to GSI Sewer Design Plans. The 1/8" = 1', and 1/12" = 1' scales are intended for cross sections that correlate to GSI Sewer Plans.

	DESIGN PLAN MULTILEADER STYLES												
NAME	ARROWHEAD SIZE	LEADER BREAK	LANDING DISTANCE	ANNOTATIVE	TEXT STYLE	ATTACHMENT	LANDING GAP	USE					
EXIST-PROF-TEXT	1.0	0.1250	2.0	NO	EX-50	Middle of top line	0.50	Existing callout for elevation view					
EXIST-SECT-TEXT	0.56	0.1250	0.5	NO	EX-40	Middle of top line	0.25	Existing callout for section view					
EXIST-TEXT	0.10	0.1250	0.1	YES	EX-100a	Middle of top line	0.10	Existing callout for plan view					
PROP-PROF-TEXT	1.0	0.1250	2.0	NO	G-50-HORIZ	Middle of top line	0.50	Proposed callout for elevation view					
PROP-SECT-TEXT	0.5	0.1250	0.5	NO	G-40	Middle of top line	0.25	Proposed callout for section view					
PROP-TEXT	0.10	0.1250	0.1	YES	G-100	Middle of top line	0.10	Proposed callout for plan view					

Note: The 1" = 20', and 1" = 30' scales are intended for use with profiles that correlate to GSI Sewer Design Plans. The 1/8" = 1', and 1/12" = 1' scales are intended for cross sections that correlate to GSI Sewer Plans.

				D	ESIGN DIME	NSION STY	LES				
NAME	ANNOTATIVE	ARROW SIZE	ARROWHEAD - USER ARROW	TEXT	LINEAR UNIT FORMAT	PRECISION	SCALE FACTOR	ANGULAR UNIT FORMAT	DECIMAL DEGREES	ZERO SUPPRESSION	USE
EX-PROF-DIMS -HORIZ	NO	1.00	_PROFILE ARROW-EX 10 SCALE HORIZ	EX-50-HORIZ	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=10' scale
EX-PROF-DIMS -HORIZ-20	NO	1.00	_PROFILE ARROW-EX 20 SCALE HORIZ	EX-50-HORIZ-20	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=20' scale
EX-PROF-DIMS -HORIZ-30	NO	1.00	_PROFILE ARROW-EX 30 SCALE HORIZ	EX-50-HORIZ-30	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=30' scale
EX-PROF-DIMS -VERT	NO	1.00	_PROFILE ARROW-EX 10 SCALE VERT	EX-50-VERT	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=10' scale
EX-PROF-DIMS -VERT-20	NO	1.00	_PROFILE ARROW-EX 20 SCALE VERT	EX-50-VERT-20	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=20' scale
EX-PROF-DIMS -VERT-30	NO	1.00	_PROFILE ARROW-EX 30 SCALE VERT	EX-50-VERT-30	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature profile view dimension at 1"=30' scale
PR-PROF-DIMS- HORIZ	NO	1.00	_PROFILE ARROW-PROP 10 SCALE HORIZ	G-50-HORIZ	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=10' scale
PR-PROF-DIMS- HORIZ-20	NO	1.00	_PROFILE ARROW-PROP 20 SCALE HORIZ	G-50-HORIZ-20	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=20' scale
PR-PROF-DIMS- HORIZ-30	NO	1.00	_PROFILE ARROW-PROP 30 SCALE HORIZ	G-50-HORIZ-30	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=30' scale
PR-PROF-DIMS- VERT	NO	1.00	_PROFILE ARROW-PROP 10 SCALE VERT	G-50-VERT	Architechural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=10' scale
PR-PROF-DIMS- VERT-20	NO	1.00	_PROFILE ARROW-PROP 10 SCALE VERT	G-50-VERT-20	Architechural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=20' scale
PR-PROF-DIMS- VERT-30	NO	1.00	_PROFILE ARROW-PROP 10 SCALE VERT	G-50-VERT-30	Architechural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature profile view dimension at 1"=30' scale
PR-DIMS	YES	0.14	N/A	G-100	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature plan view dimension
EX-SECT-DIMS	NO	0.56	N/A	EX-40	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature section view dimension at 1/4"=1' scale
EX-SECT-DIMS 1-8	NO	1.12	N/A	EX-80	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature section view dimension at 1/8"=1' scale
EX-SECT-DIMS 1-12	NO	1.68	N/A	EX-120	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Existing feature section view dimension at 1/12"=1' scale
PR-SECT-DIMS	NO	0.56	N/A	G-40	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature section view dimension at 1/4"=1' scale
PR-SECT-DIMS 1-8	NO	1.12	N/A	G-80	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature section view dimension at 1/8"=1' scale
PR-SECT-DIMS 1-12	NO	1.68	N/A	G-120	Architectural	0'-0"	12	Decimal Degrees	0	1 feet, 0 inches	Proposed feature section view dimension at 1/12"=1' scale

Note: The 1" = 20', and 1" = 30' scales are intended for use with profiles that correlate to GSI Sewer Design Plans. The 1/8" = 1', and 1/12" = 1' scales are intended for cross sections that correlate to GSI Sewer Plans.

# **APPENDIX D: DYNAMIC BLOCK FUNCTIONS**

#### **Dynamic Block Functions**

#### Visibility




The visibility grip allows the drafter to toggle between various visibility states defined within a block. This function essentially allows multiple blocks to be stored within one block by either hiding or showing particular geometry in a

visibility state.

By clicking on the triangular visibility grip, the drafter may choose which visibility state is to show. For example, the highway grate inlet block illustrates the usefulness of visibility states by storing variations of the inlet within the same block.

# DEFAULT SIZE / TRAP ON DEFAULT SIZE / TRAP OFF EX. INLET / TRAP ON EX. INLET / TRAP OFF 3 INCH RISER 5.5 INCH RISER 8 INCH RISER PRECAST RISER (2 FEET)

#### Move Action




The dynamic block move action is associated with two types of grips, an arrowhead shape or a light blue square. Notice that the square grip is a slightly different color than the darker blue square block insert grip. The move action will drag an assigned portion of the block geometry to the location of your choice. It is common for text within blocks

to be associated with a move action so that it may be relocated without moving the entire block. Move actions using the square grip allow for geometry to be moved in any direction while move actions using the arrowhead shape constrain the move to a defined axis or along a linear path between two points.

#### Stretch Action

The stretch action uses the same two types of grips as the move action; however, more commonly the arrowhead shape is used. The stretch action will elongate or shorten the associated geometry within the block. This is useful for the cleanout shown below as the cleanout's geometry is dependent on the depth of the pipe it is connecting to.



#### Scale Action



The scale action uses the same two grip types as the move and stretch action. The scale action will enlarge or shrink the associated block geometry uniformly.

#### **Rotate Action**



The rotate action uses a circle grip to rotate the associated geometry within the block. Some dynamic blocks are designed to rotate all geometry within the block while others may only have certain objects associated with the dynamic rotate function. If a dynamic block has a rotate action grip, it should be used instead of utilizing AutoCAD's rotate command.

Flip Action




The flip action uses an arrow shaped grip to flip the associated geometry within the block along an axis perpendicular to the arrow alignment. A dynamic block may contain multiple flip actions each associated with different geometry within the block.

#### Alignment Action




The alignment action grip will align the block parallel or perpendicular, depending on how the block is set-up, to another object. The grip may be used to move the block near the

object to be used for alignment. The block will rotate accordingly when the grip moves over or snaps to the object. Please note, the direction in which the block is brought toward the reference object will determine along which side the block is aligned.




#### **Attribute Text**

Attribute text is pre-defined within a block as a placeholder for the user to customize after the block is inserted into the drawing. Upon the insertion of the block, the user will be prompted to define what text value the attribute should display or the user may choose to insert the block with its default text value.




Attribute text may be edited at any time by double-clicking the block which will cause the "Enhanced Attribute Editor" window to display. Changing the value of the attribute will edit what text is displayed.



In the next tab, "Text Options", the user may edit the format of the text displayed by the attribute. Attributes may be made annotative and the rotation may be changed to different values for different scales within the text options tab.

#### Annotative Text within Blocks

Many common symbols may be made into blocks to save time in



drafting. Some symbols are grouped with simple text of a constant value that should display upright in all plan views. Annotative text may be set to match orientation to layout so that it will scale and rotate automatically to



display upright and at the correct size within a paper-space viewport that is set to a certain scale and user coordinate system (UCS).

Blocks containing annotative text set to match orientation to layout should not be rotated using AutoCAD's rotate command. This changes the direction the text recognizes as upright to the angle that the block has been rotated to. Blocks may be rotated using the dynamic rotate grip and the text will remain upright as the block geometry rotates.


Annotative text set to match orientation to layout will only automatically rotate when viewed through a paper-space viewport and will display in model space at the orientation in which it was inserted. It is recommended that all blocks with this type of text are inserted while in the defined "Plan" UCS. As opposed to the "World" UCS where the site is aligned by true coordinates, the "Plan" UCS shall best orient the site as it should be displayed on the location plan.

**APPENDIX E: RECOMMENDED DRAFTING TIPS** 


#### **EXTERNAL REFERENCING - TITLE BLOCK EXAMPLE**

When externally referencing (xref) the title block, it is recommended to xref it into paper space within the prepared layout tab. If additional layout tabs are created, the referenced title block may be copied and pasted to additional layout tabs in a drawing.

- 1. Open the layout drawing into which the title block is to be inserted and navigate to the paperspace layout.
- 2. Open the xref manager (Command: "xref") and click to insert a .dwg reference.
- 3. Navigate to the copy of the "PWD GSI Title Block.dwg" file that you have saved in your project file location and named using the proper file naming convention for the project and select to open.
- 4. Accept the default settings as shown below:




- 5. To insert the title block attributes that pair with the title block border, use the "Insert" command and select browse to navigate to the "PWD GSI Drawing Border Attributes 2021.dwg" file and select to open.
- 6. Please accept the default settings as shown below:



7. Upon block insertion you will be prompted to fill out the project information or accept the default values.

Please note that the above instructions to add an external reference also apply to other types of external reference files. To add references to model space, make model space active before adding the reference file and ensure that you are in the "World" User Coordinate System (UCS). It is recommended that references be inserted using the "Overlay" reference type.

## **WORKING IN DESIGN CENTER**



- 1. Open the Design Center by typing "DC" in the command line.
- 2. Under the "Folders" tab on the left, navigate to the block library\*.
- 3. Expand the library and select "Blocks".
- 4. Once the blocks load to the right, select the block you would like to insert and drag it from the design center dialogue into your drawing's model or paperspace.


\*Note: It is strongly recommended that the block libraries be saved locally to a user's hard drive rather than a network folder when utilizing Design Center. Saving to a network folder may cause lag and non-responsiveness. A default local drive location for files to be accessed through design center is "C:\Program Files\Autodesk\<Select Year Version>\Sample\ en-us\DesignCenter" in a typical AutoCAD installation. Please note that you will need to replace <Select Year Version> with your version of AutoCAD.

### INSERTING BLOCKS CONTAINING MATCH-ORIENTATION-TO-LAYOUT TEXT

Many of the blocks containing text placed in plan view contain annotative text that will automatically rotate to display horizontally when viewed through a paperspace viewport. In this case it is the User Coordinate System (UCS) set to the viewport that determines the rotation automatically. In order for this to work properly, blocks of this type must be inserted in a certain manner.

To determine which blocks contain match-orientation-to-layout text, see Appendix A for the complete block library. Blocks marked with an asterisk (\*) contain this type of text.

1. Ensure that the UCS is set to "World". Find the area in which the blocks are to be inserted.




2. Insert the desired block using the "insert" command and place it at the desired location. If the block is not yet loaded in the drawing it will need to be brought in. See the "Working in Design Center" drafting tip in this Appendix for the recommended method.

3. While still in model space, switch to a UCS aligned as the plan will be shown on the layout. You will notice that the text will still be aligned such that it would display horizontally in the world UCS. This is correct for the text, however certain symbols will not be aligned as they should. Use the dynamic rotate grip provided to align symbols as desired.

NOTE: Only rotate with the dynamic grip, not the rotate command.




4. Switch to a layout and view the blocks through a viewport. The text should now view horizontally in any UCS. If the text is in conflict with any other item, move the text with the provided dynamic move grip.




### **CUSTOM INLET STYLE GUIDE**

- 1. While in model space, import any of the inlet blocks. It is recommended that this be done through the Design Center. Refer to the "WORKING IN DESIGN CENTER" drafting tip in this Appendix.
- 2.For this example, the "OMG INLET PROFILE" and "OMG INLET SECTION" blocks are used.
- 3. For each block, select the "CUSTOM WITH TRAP" visibility state as shown below:




4. This will result in an inlet with a trap that can be adjusted by selecting the associated grip and moving the trap up or down. You also have the option to adjust the sump using the Stretch Action by selecting the grip and pulling it up or down. Note that wherever the trap is placed in section view, the profile view will need to be adjusted accordingly to match inverts, as this is not an automated feature.




### **ADDING SCALES TO ANNOTATIVE ATTRIBUTES**

1. Blocks with annotative attribute text will insert to the correct size for the scale at which it is inserted. Any additional desired scales must be added as shown below. In this example, the "Tree Pit" block is used.




2. Isolate the blocks to which annotation scales will be added. The layer on which the block is inserted as well as the layer(s) used inside of the block must be turned on while all others are turned off or frozen. The layers within the block can be viewed using the "xlist" command.




3. If the block is inserted at 10 scale, the text will size for that scale only. If switched to 20 scale, the text size will not change.




4. Switch back to the scale at which the block was inserted. Enable the function to automatically add scales to annotative objects when the annotation scale changes, as shown below.



5. Switch to the scale which you wish to add to the block. The text should now size appropriately for that scale.



6. After the desired scales have been added, turn off the function to automatically add scales. The previously turned off or frozen layers may now be turned back on. Adjust text location for newly added scales.




### CHANGING A MULTILEADER HEAD TO MEDIUM DOT


1. Select the multileader for which you would like to change the leader head. In most cases, a triangle arrowhead is used, however certain applications merit the use of a dot leader head. In cases where it is difficult to point to an outline, the dot leader is used to point to the internal area of the feature.



2. Open the properties dialog. Under the "Leaders" section find the line that says "Arrowhead." Click on the drop down menu and select "User Arrow".



3. When the "Select Custom Arrow Block" window appears, choose "\_DotMedium" from the dropdown menu and click OK.




4. The leader head should now show a dot instead of the standard triangle arrowhead. Adjust the leader head to point to a location within the internal area of the object that is being called out.



### Scaling a Profile at 1"=10' Horizontal Scale and 1"=5' Vertical Scale

1. In order to ease the drafting process and future revisions, it is recommended that profile/elevation views be drawn at a 1:1 ratio and then vertically stretched by a factor of two. First, select all objects for the profile excluding the title label.




2. Activate the "block" command, and the block definition window will display. Ensure that the box to specify the base point on-screen is selected as well as allowing exploding. Ensure that the box to scale uniformly is not selected. It is recommended that you choose a base point that is consistent between multiple profiles. In this example, the top of the stone trench on the left is chosen.



3. Select the newly-created profile block and open the properties menu. Under the "Geometry" section, change the Scale Y value to 2 to vertically stretch the block.


Block Reference General ☐ ByLayer Color Linetype ByLayer 1.0000 Linetype scale ByColor ByLayer Lineweight Transparence ByLayer Hyperlink 3D Visualization Material ByLaver Position X 37,7230 Position Y -158.3578 Position Z 0.0000 Scale X 1.0000 1.0000 Scale Z 1.0000 SYSTEM 1 Rotation 134 No Annotative **Block Unit** Feet Unit factor 1.0000

4. Now if displayed through a 10 scale viewport, the vertical scale of the profile will be at 5 scale.



Note: Changes to the profile may be made in the block editor or the block may be exploded. Before exploding the block, be sure to change the "Scale Y" back to 1.


## **GRAY SCALING FEATURES SEPARATED BY A MATCHLINE**



- 1. Copy an existing viewport over top of itself.
- 2. Clip the two viewports to share a common edge (the matchline).
- 3. Activate the viewport containing the layer(s) to be shown as gray.
- 4. Open the layer properties manager.
- 5. Select the layer(s) to be shown as gray.
- 6. Change the VP color to #8.

### **PLOTTING**

- 1. Please note that all three templates are preset to print using the provided plot style and default "DWG to PDF.pc3" PDF creator (An Autodesk default PDF publisher). Furthermore, paper size, plot scale, plot offset drawing orientation and other plot options have been pre-defined within the templates.
- 2. It is the user's responsibility to save the provided plot style to the appropriate location on their computer in order for it to map correctly within AutoCAD. See the "PWD GSI CAD Standards Support File Instructions for AutoCAD" document in the SUPPORT FILES folder for instructions on how to load the appropriate plot style into AutoCAD.
- 3. Accept the default values and press OK to create a full-size PDF. It is recommended to plot from the PDF rather than directly from AutoCAD to maintain consistency. Furthermore, printing half-size or 11x17 prints from the PDF maintains the lineweight scale. If you choose to plot directly to your own plotter, please be mindful of the plot area and select the appropriate size paper to print.




\*Note: Some PDF programs may experience errors with certain AutoCAD entities like wipeouts and some hatches. If you notice your drawings are not plotting as they should, for example inconsistently darkened and thickened linework or missing hatching sections, please plot directly to your printer/plotter. If a digital file like a PDF is desired, Review and printed to PDF from there. This will please utilize the "DWF6 ePlot.pc3" print driver. The .dwf file may be opened with Autodesk Design prevent printing errors that may occur with certain PDF software.

### "ETRANSMIT" TRANSMITTAL GUIDE

The "Etransmit" function in AutoCAD will automatically package files dependent on a layout drawing. Each layout drawing to be submitted to PWD will need to be "Etransmitted" separately.

- 1. Open the layout drawing and ensure that there are no unreferenced files. You may check by opening the file references window using the "XREF" command. Unreferenced files are listed as unreferenced in the file status column of the file references window.
- 2. Once satisfied with the state of the drawing, save the drawing and then use the "Etransmit" command. The "Create Transmittal" window will appear.



- 3. Review the files tree and ensure that all filenames follow the file naming convention.
- 4. Click the "OK" button to complete the "Etransmit". A window will appear to browse to the location where you would like the transmittal to be saved.
- 5. Once complete, the "Etransmit" will have saved a .zip file to the save location you selected. This .zip file along with any additional .zip files for each layout drawing transmittal should be sent to PWD.
- 6. The "Etransmit" .zip file will be extracted by the recipient. All external references will automatically map to the layout drawing.

IMPORTANT: Once the "Etransmit" .zip file is created, no files within should be renamed, moved, added, or deleted. This will interfere with the automatic remapping of external references when the .zip file is extracted.

### **APPENDIX F: EXAMPLE PLANS**

### The following example plans have been provided:

### T-1 INDEX SHEET

Title Sheet

### (30%) BASEPLAN

Detailed Survey Sheet

### PRELIMINARY DESIGN (50%) UTILITY & GRADING PLAN

- Rain Garden
- Fully Lined Tree Trench

### SUBSTANTIALLY COMPLETE DESIGN (70%) UTILITY & GRADING PLAN

- Rain Garden
- Fully Lined Tree Trench
- Construction Details Sheet
- Large Area Disconnection

### PRE-FINAL (90%) DESIGN

Partially Lined Tree Trench

### LANDSCAPE PLANS

- Rain Garden
- Tree Trench
- Landscape Details Sheet

### DRAINAGE AREA MAP

# CITY OF PHILADELPHIA

# PHILADELPHIA — DEPARTMENT—

**DRAWINGS FOR:** GREEN STORMWATER INFRASTRUCTURE PROJECT BERKS AND SEDGLEY GREENING **PWD WORK NO. S-50179-G** 

SHEET INDEX				
SHEET NO.	TITLE			
T-1	GREEN STORMWATER INFRASTRUCTURE INDEX SHEET			
G-1	GRADING AND UTILITY PLAN - SYSTEM 1288-01			
G-2	GRADING AND UTILITY PLAN - SYSTEM 1288-01			
G-3	GRADING AND UTILITY PLAN - SYSTEM 1288-02			
G-4	GRADING AND UTILITY PLAN - SYSTEM 1288-03			
G-5	GRADING AND UTILITY PLAN - SYSTEM 1288-04			
G-6	SITE PLAN - SYSTEM 1288-05			
G-7	GRADING AND UTILITY PLAN - SYSTEM 1288-05			
G-8	GRADING AND UTILITY PLAN - SYSTEM 1288-05			
G-9	GRADING AND UTILITY PLAN - SYSTEM 1288-05			
G-10	GRADING AND UTILITY PLAN - SYSTEM 1288-06			
G-11	GRADING AND UTILITY PLAN - SYSTEM 1288-07			
G-12	GRADING AND UTILITY PLAN - SYSTEM 1288-09			
G-13	GRADING AND UTILITY PLAN - SYSTEM 1288-10			
G-14	GRADING AND UTILITY PLAN - SYSTEM 1288-11			
G-15	GRADING AND UTILITY PLAN - SYSTEM 1288-12			
G-16	CONSTRUCTION DETAILS 1			
G-17	CONSTRUCTION DETAILS 2			
G-18	CONSTRUCTION DETAILS 3			
G-19	CONSTRUCTION DETAILS 4			

# GENERAL NOTES:

- ALL DISTANCES SHOWN ARE IN DISTRICT STANDARD MEASUREMENT. PAYMENT FOR ALL WORK WILL BE BASED UPON THAT STANDARD.
- THE LOCATIONS AND ELEVATIONS OF THE EXISTING UTILITIES ARE APPROXIMATE. THE ELEVATIONS OF THE EXISTING UTILITIES MUST BE FIELD CHECKED DURING CONSTRUCTION.
- ALL SIDEWALK AND CURBING TO BE REPLACED IN KIND ALONG FULL LIMITS OF CONSTRUCTION TO NEXT EXISTING JOINT OR AS DIRECTED BY PWD.
- WELDED PIPE BOOT SEAL MUST BE INSTALLED AT ANY POINT WHERE A PIPE PENETRATES GEOMEMBRANE LINER.
- SUFFICIENT EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE INSTALLED AND MAINTAINED BY THE CONTRACTOR AS TO PREVENT STANDING WATER OR SEDIMENTATION OF STORMWATER SYSTEMS. SYSTEMS DETERMINED BY PWD TO BE INADEQUATELY PROTECTED AND THEREBY COMPROMISED WILL BE REPLACED TO THE EXTENT REQUIRED BY PWD (UP TO AND INCLUDING FULL REPLACEMENT) AT NO
- ORIFICE SHOULD NOT BE DRILLED PRIOR TO AUTHORIZATION BY PWD. PWD WILL REVIEW THE RESULTS OF THE DOUBLE RING INFILTROMETER TESTS CONDUCTED AFTER SMP EXCAVATION AND WILL CONFIRM ORIFICE DIMENSIONS.
- EROSION CONTROL MATTING SHALL BE PLACED OVER ALL SOIL SURFACES NOT STABILIZED BY PLANTING.
- SUPPORT AND PROTECT ALL UTILITIES, UTILITY POLES, OVERHEAD WIRES, TRAFFIC SIGNAGE, TRAFFIC SIGNALS, AND STREET LIGHTING WITHIN THE LIMITS OF WORK.
- . VERTICAL DATUM IS ON CITY OF PHILADELPHIA DATUM
- O. LINE AND GRADE STAKES FOR CURB, PAVING, ETC. WILL BE FURNISHED BY THE 9TH SURVEY DISTRICT OF THE CITY OF PHILADELPHIA. CONTACT INFORMATION: 9TH SURVEY DISTRICT, 4000 N. AMERICAN ST., PHILA., PA, 19140, (215) 685-3050
- NOTIFY THE 9TH SURVEY DISTRICT A MINIMUM OF TWO (2) WEEKS PRIOR TO THE START OF WORK TO SCHEDULE A TIME FOR CURB STAKE LAYOUT SERVICES.



Compliant Curb Ramp

Tree/Trunk Size in "

⊕10" Stump Tree Stump w/ Trunk in " Existing Pavement Markings

Trash Receptacle

√ +xx.xx Existing Spot Elevation

TS +XX.XX Existing Top/Bottom of Step TC +XX.XX Existing Top/Bottom of Curb

------ Right-of-Way Line

o—o Bike Rack

C. Curb Concrete Curb G. Curb Granite Curb

Dep. Curb Depressed Curb

St. Wall Stone Wall

C. Wall Concrete Wall

S.R.E. Sewer Return Elevation

S.R.L. Sewer Return Location

<del>x x x</del> Fence

Parking Meter

Parking Kiosk

Verizon Juction Box

Electrolysis Test Station

City Inlet (4 Denotes 4 FT, 6 Denotes 6 FT)

Old City Inlet(#1,#2,#3 or #4 Denotes Size)

(Above Ground)

Fire Hydrant

Gas Valve

Door Sill

Clean Out

# GREEN STORMWATER INFRASTRUCTURE PROJECT INDEX SHEET

BERKS AND SEDGLEY GREENING

SUPERVISOR

DATE


PHILADELPHIA


PLAN PREPARED FOR THE CITY OF PHILADELPHIA WATER DEPARTMENT BY:


**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

> DRAFT < MILESTONE > INSERT COMPANY LOGO AND ADDRESS HERE SUBMISSION <DATE>

CITY OF PHILADELPHIA WATER DEPARTMENT CONSULTING ENGINEERING FIRM 1" = 300' DEPUTY COMMISSIONER, PLANNING & ENVIRONMENTAL SERVICES WATER COMMISSIONER PROJECT. ENGR. PROJECT. ENGR. XXX XXXX SHEET NO. T-1 OF







**COMPONENT ID** 

COMPONENT TYPE

GREEN HWY GRATE INLET

**DISTRIBUTION PIPE** 

OBSERVATION WELL

CITY INLET

UNDERDRAIN


CLEANOUT

CLEANOUT

CONTROLLING BENCH MARK

F. Hyd. rim on the intersection of Rising Sun Avenue and Godfrey Street Elev. = 121.29

# PROPOSED LEGEND



NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST

3 DAYS PRIOR TO EXCAVATION HIGHWAY DISTRICT NO. SURVEY DISTRICT NO. OUTFALL NO.

T-06 PA ONE CALL <u>20152221447</u>

# GREEN STORMWATER INFRASTRUCTURE PROJECT

LAWNCREST STREETS SOUTHWEST GRADING & UTILITY PLAN- SYSTEM 1139-06 HASBROOK AVENUE

E. SANGER ST. TO SENTNER ST.

CITY OF PHILADELPHIA APPROVED WATER DEPARTMENT CONSULTING ENGINEERING FIRM SCALES: 1"=10' PROFILE HORIZ. N/A N/A SECTION N/A

PHILADELPHIA

- DEPARTMENT-PLAN PREPARED FOR THE CITY OF PHILADELPHIA WATER DEPARTMENT BY:

**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

PIPE LENGTH (FT)

N/A

N/A

31

57

N/A

DRAFT PRELIMINARY DESIGN

SUBMISSION <DATE>

INSERT COMPANY LOGO WORK NO. S-50179-G SHEET NO. G-13 OF 67 SHEETS

PROJECT. ENGR. PROJECT. ENGR. XXX XXXX


OVERHEAD WIRES ON EAST SIDE OF HASBROOK AVENUE AND NORTH SIDE OF EAST SANGER STREET

# GENERAL NOTES:

- ALL DISTANCES SHOWN ARE IN DISTRICT STANDARD MEASUREMENT. PAYMENT FOR ALL WORK WILL BE BASED UPON THAT STANDARD.
- THE LOCATIONS AND ELEVATIONS OF THE EXISTING UTILITIES ARE APPROXIMATE. THE ELEVATIONS OF THE EXISTING UTILITIES MUST BE FIELD CHECKED DURING CONSTRUCTION.
- ALL SIDEWALK AND CURBING TO BE REPLACED IN KIND ALONG FULL LIMITS OF CONSTRUCTION TO NEXT EXISTING JOINT OR AS DIRECTED BY PWD.
- WELDED PIPE BOOT SEAL MUST BE INSTALLED AT ANY POINT WHERE A PIPE
- PENETRATES GEOMEMBRANE LINER. SUFFICIENT EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE INSTALLED AND MAINTAINED BY THE CONTRACTOR AS TO PREVENT STANDING WATER OR SEDIMENTATION OF STORMWATER SYSTEMS. SYSTEMS DETERMINED BY PWD TO BE INADEQUATELY PROTECTED AND THEREBY COMPROMISED WILL BE REPLACED TO THE EXTENT REQUIRED BY PWD (UP TO AND INCLUDING FULL REPLACEMENT) AT NO
- ORIFICE SHOULD NOT BE DRILLED PRIOR TO AUTHORIZATION BY PWD. PWD WILL REVIEW THE RESULTS OF THE DOUBLE RING INFILTROMETER TESTS CONDUCTED AFTER SMP EXCAVATION AND WILL CONFIRM ORIFICE DIMENSIONS.
- EROSION CONTROL MATTING SHALL BE PLACED OVER ALL SOIL SURFACES NOT STABILIZED BY PLANTING.
- SUPPORT AND PROTECT ALL UTILITIES, UTILITY POLES, OVERHEAD WIRES, TRAFFIC SIGNAGE, TRAFFIC SIGNALS, AND STREET LIGHTING WITHIN THE LIMITS OF WORK.
- . VERTICAL DATUM IS ON CITY OF PHILADELPHIA DATUM.


ADDITIONAL COST TO PWD.


- O. LINE AND GRADE STAKES FOR CURB, PAVING, ETC. WILL BE FURNISHED BY THE 5TH SURVEY DISTRICT OF THE CITY OF PHILADELPHIA. CONTACT INFORMATION: 5TH SURVEY DISTRICT, 6601 RISING SUN AVE., PHILA., PA, 19111, (215) 685-0585.
- NOTIFY THE 5TH SURVEY DISTRICT A MINIMUM OF TWO (2) WEEKS PRIOR TO THE START OF WORK TO SCHEDULE A TIME FOR CURB STAKE LAYOUT SERVICES.



CONTROLLING BENCH MARK

P.K. Nail at the Intersection of 32nd St. and Susquehanna Ave. Elevation = +112.35P.K. Nail at the Intersection of 33rd St. and Montgomery Ave. Elevation = +111.67P.K. Nail at the Intersection of 30th St. and Sedgley Ave. Elevation = +101.34





# GENERAL NOTES:

- ALL DISTANCES SHOWN ARE IN DISTRICT STANDARD MEASUREMENT. PAYMENT FOR ALL WORK WILL BE BASED UPON THAT STANDARD.
- 2. THE LOCATIONS AND ELEVATIONS OF THE EXISTING UTILITIES ARE APPROXIMATE. THE ELEVATIONS OF THE EXISTING UTILITIES MUST BE FIELD CHECKED DURING
- . ALL SIDEWALK AND CURBING TO BE REPLACED IN KIND ALONG FULL LIMITS OF CONSTRUCTION TO NEXT EXISTING JOINT OR AS DIRECTED BY PWD.
- . WELDED PIPE BOOT SEAL MUST BE INSTALLED AT ANY POINT WHERE A PIPE PENETRATES GEOMEMBRANE LINER.
- SUFFICIENT EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE INSTALLED AND MAINTAINED BY THE CONTRACTOR AS TO PREVENT STANDING WATER OR SEDIMENTATION OF STORMWATER SYSTEMS. SYSTEMS DETERMINED BY PWD TO BE INADEQUATELY PROTECTED AND THEREBY COMPROMISED WILL BE REPLACED TO THE EXTENT REQUIRED BY PWD (UP TO AND INCLUDING FULL REPLACEMENT) AT NO ADDITIONAL COST TO PWD.
- ORIFICE SHOULD NOT BE DRILLED PRIOR TO AUTHORIZATION BY PWD. PWD WILL REVIEW THE RESULTS OF THE DOUBLE RING INFILTROMETER TESTS CONDUCTED

AFTER SMP EXCAVATION AND WILL CONFIRM ORIFICE DIMENSIONS.

- EROSION CONTROL MATTING SHALL BE PLACED OVER ALL SOIL SURFACES NOT STABILIZED BY PLANTING.
- 8. SUPPORT AND PROTECT ALL UTILITIES, UTILITY POLES, OVERHEAD WIRES, TRAFFIC SIGNAGE, TRAFFIC SIGNALS, AND STREET LIGHTING WITHIN THE LIMITS OF WORK.
- 9. VERTICAL DATUM IS ON CITY OF PHILADELPHIA DATUM
- 10. LINE AND GRADE STAKES FOR CURB, PAVING, ETC. WILL BE FURNISHED BY THE 9TH SURVEY DISTRICT OF THE CITY OF PHILADELPHIA. CONTACT INFORMATION: 9TH SURVEY DISTRICT, 4000 N. AMERICAN ST., PHILA., PA, 19140, (215) 685-3050
- 11. NOTIFY THE 9TH SURVEY DISTRICT A MINIMUM OF TWO (2) WEEKS PRIOR TO THE START OF WORK TO SCHEDULE A TIME FOR CURB STAKE LAYOUT SERVICES.

NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST

3 DAYS PRIOR TO EXCAVATION 

 HIGHWAY DISTRICT NO.
 03
 WARD NOMBER
 20160991580

 SURVEY DISTRICT NO.
 09
 DRAINAGE SHT. NO.
 40 & 41
 20160991611

 OUTFALL NO.
 D39 & S05
 PA ONE CALL
 20160991626

# GREEN STORMWATER INFRASTRUCTURE PROJECT

BERKS AND SEDGLEY GREENING GRADING AND UTILITY PLAN SYSTEM 1288-05 - N. 30TH STREET EUCLID AVE TO W. BERKS ST

PLAN PREPARED FOR THE CITY OF PHILADELPHIA WATER DEPARTMENT BY:	APPROVED	CONSULTING ENGINEERING FIRM

WATER DEPARTMENT SCALES: PROFILE HORIZ.

CITY OF PHILADELPHIA

1"=10'

1"=10'

1/4"=1'-0"

1"=5"

WORK NO. S-50179-GSHEET NO. G-8 OF 19 SHEETS

PROJECT. ENGR. PROJECT. ENGR. XXX XXXX


DRAFT SUBSTANTIALLY COMPLETE INSERT COMPANY LOGO AND ADDRESS HERE **DESIGN SUBMISSION <DATE>** 


**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** 

AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS

PHILADELPHIA





WATER DEPARTMENT BY:

SHEET NO. G-19 OF 22 SHEETS

PROJECT. ENGR. PROJECT. ENGR. XXX XXXX

DRAFT SUBSTANTIALLY COMPLETE INSERT COMPANY LOGO WORK NO. S-50179-G

**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** 

**DESIGN SUBMISSION < DATE>** 

AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS

EXISTING PAVEMENT

**CONCRETE APRON** 

SCALE: N.T.S.

MAXIMUM SLOPE OF APRON PARALLEL TO CURB IS 7H:1V

MAXIMUM SLOPE OF APRON PERPENDICULAR TO CURB

IS 7H:1V (15.0%), 12H:1V (8.5%) IS PREFERRED.

3. CONCRETE APRON THICKNESS TO MATCH BOTTOM OF

4. CONCRETE BASE COURSE MINIMUM THICKNESS IS 8" ON

(15.0%), 12H:1V (8.5%) IS PREFERRED

EXISTING CONCRETE BASE COURSE.

CITY STREETS AND 10" ON STATE ROUTES.

UPSTREAM ELEVATION

COLLAR MATERIAL SHALL BE RIGID POLYETHYLENE SHEET.

STAINLESS STEEL SHALL BE GRADE 304 OR BETTER.

CONNECTING BAND SHALL BE SEALED AT BOTH ENDS WITH CAULK OR MASTIC.


DIMENSION "W" SHALL BE 3 TIMES THE DIAMETER OF THE INTERSECTING PIPE.

5. ONE COLLAR WITH TWO HOLES MAY BE USED WHEN CLOSE PARALLEL PIPES ARE INSTALLED.

**ANTI-SEEP COLLAR** 

SCALE: N.T.S.

SECTION A-A



- ALL DISTANCES SHOWN ARE IN DISTRICT STANDARD MEASUREMENT. PAYMENT FOR ALL WORK WILL BE BASED UPON THAT STANDARD.
- THE LOCATIONS AND ELEVATIONS OF THE EXISTING UTILITIES ARE APPROXIMATE. THE ELEVATIONS OF THE EXISTING UTILITIES MUST BE FIELD CHECKED DURING CONSTRUCTION.
- ALL SIDEWALK AND CURBING TO BE REPLACED IN KIND ALONG FULL LIMITS OF CONSTRUCTION TO NEXT EXISTING JOINT OR AS DIRECTED
- WELDED PIPE BOOT SEAL MUST BE INSTALLED AT ANY POINT WHERE A PIPE PENETRATES GEOMEMBRANE LINER.
- SUFFICIENT EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE INSTALLED AND MAINTAINED BY THE CONTRACTOR AS TO PREVENT STANDING WATER OR SEDIMENTATION OF STORMWATER SYSTEMS. SYSTEMS DETERMINED BY PWD TO BE INADEQUATELY PROTECTED AND THEREBY COMPROMISED WILL BE REPLACED TO THE EXTENT REQUIRED BY PWD (UP TO AND INCLUDING FULL REPLACEMENT) AT NO ADDITIONAL COST TO PWD.
- ORIFICE SHOULD NOT BE DRILLED PRIOR TO AUTHORIZATION BY PWD. PWD WILL REVIEW THE RESULTS OF THE DOUBLE RING INFILTROMETER TESTS CONDUCTED AFTER SMP EXCAVATION AND WILL CONFIRM ORIFICE DIMENSIONS.
- EROSION CONTROL MATTING SHALL BE PLACED OVER ALL SOIL SURFACES NOT STABILIZED BY PLANTING.
- SUPPORT AND PROTECT ALL UTILITIES, UTILITY POLES, OVERHEAD WIRES, TRAFFIC SIGNAGE, TRAFFIC SIGNALS, AND STREET LIGHTING WITHIN THE LIMITS OF WORK.
- VERTICAL DATUM IS ON CITY OF PHILADELPHIA DATUM.
- O. LINE AND GRADE STAKES FOR CURB, PAVING, ETC. WILL BE FURNISHED BY THE 5TH SURVEY DISTRICT OF THE CITY OF PHILADELPHIA. CONTACT INFORMATION: 5TH SURVEY DISTRICT, 6601 RISING SUN AVE., PHILA., PA, 19111, (215) 685-0585.
- NOTIFY THE 5TH SURVEY DISTRICT A MINIMUM OF TWO (2) WEEKS PRIOR TO THE START OF WORK TO SCHEDULE A TIME FOR CURB STAKE LAYOUT SERVICES.

				VERTICAL SCALE: 1" = 5'-0"		
	STRUCTURES					
#	COMPONENT ID	COMPONENT TYPE	GRATE/RIM ELEV.	OUT INV. ELEV.		
1		GREEN CITY INLET	+69.27	+66.27		
2		GREEN CITY INLET	+71.07	+68.07		
3		GREEN CITY INLET	+73.20	+70.20		
4		GREEN HWY GRATE INLET	+67.06	+64.56		
5		GREEN HWY GRATE INLET	+66.71	+64.21		
6		GREEN HWY GRATE INLET	+69.60	+65.60		
7		GREEN HWY GRATE INLET	+69.48	+66.98		
8		GREEN HWY GRATE INLET	+71.68	67.68		
9		GREEN HWY GRATE INLET	+71.22	+68.72		
10		GREEN HWY GRATE INLET	+72.90	+70.40		
11		GREEN HWY GRATE INLET	+72.76	+70.26		
12		GREEN HWY GRATE INLET	+72.83	+70.33		
13		GREEN DUAL CATCH BASIN HWY GRATE INLET	+69.12	+66.62 (TO GSI SEWER); +64.12 (TO SEWER)		
14		GREEN DUAL CATCH BASIN HWY GRATE INLET	+70.74	+68.24 (TO GSI SEWER); +65.74 (TO SEWER)		
15		HWY GRATE INLET	+69.56	+64.56		
16		HWY GRATE INLET	+69.18	+64.18		
17		HWY GRATE INLET	+70.95	+65.95		
18		HWY GRATE INLET	+70.83	+65.83		
19		CITY INLET	+69.30	+64.30		
20		CITY INLET	+71.30	+66.30		
21		SW MANHOLE	+66.91	SEE PLAN FOR ELEVATIONS		
22		SW MANHOLE	+69.46	SEE PLAN FOR ELEVATIONS		
23		SW MANHOLE	+71.29	SEE PLAN FOR ELEVATIONS		
24		SW MANHOLE	+72.84	SEE PLAN FOR ELEVATIONS		

	PIPES				
#	COMPONENT ID	COMPONENT TYPE	PIPE SIZE/DIA. (IN)	PIPE LENGTH (FT)	
25		GSI SEWER	14" x 23"	246	
26		GSI SEWER	15"	167	
27		GSI SEWER	12"	199	
28		DISTRIBUTION PIPE	8"	7	
29		DISTRIBUTION PIPE	8"	17	
30		DISTRIBUTION PIPE	8"	43	
31		DISTRIBUTION PIPE	8"	34	
32		DISTRIBUTION PIPE	8"	5	
33		DISTRIBUTION PIPE	8"	17	
34		DISTRIBUTION PIPE	8"	55	
35		DISTRIBUTION PIPE	8"	38	
36		DISTRIBUTION PIPE	8"	5	
37		DISTRIBUTION PIPE	8"	15	
38		DISTRIBUTION PIPE	8"	47	
39		DISTRIBUTION PIPE	8"	50	
40		DISTRIBUTION PIPE	8"	25	
41		DISTRIBUTION PIPE	8"	9	

NOTE: PIPES CONNECTING GREEN INLETS TO GSI SEWER MAIN ARE DUCTILE IRON PIPE UNLESS INDICATED OTHERWISE.

> **EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

DRAFT SUBSTANTIALLY COMPLETE **DESIGN SUBMISSION <DATE>** 



GSI SEWER TO SMP 1267-01-01 HAWTHORNE STREET COMLY ST. TO BENNER ST.

HIGHWAY DISTRICT NO.

CITY OF PHILADELPHIA WATER DEPARTMENT CONSULTING ENGINEERING FIRM SCALES: PLAN 1"=30' PROFILE HORIZ. 1"=30' 1"=5' SECTION 1/8"=1'-0"

NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR

SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST

3 DAYS PRIOR TO EXCAVATION

DRAINAGE SHT. NO. 72

 SURVEY DISTRICT NO.
 05
 DIVAINAGE SITE NO.
 —
 20160693295

 OUTFALL NO.
 F21
 PA ONE CALL
 20160693411

GREEN STORMWATER INFRASTRUCTURE PROJECT

WISSINOMING PARK

INSERT COMPANY LOGO WORK NO. S-50179-G AND ADDRESS HERE

SHEET NO. G-26 OF XX SHEETS

DRAWN BY Ixxx xxxx PROJECT. ENGR. Ixxx xxxx

┌3'H Br. Wall

∤ \_2 Story Brick

3'-0" Cover

~4' GREEN HWY


**GRATE INLET** 

20160200724

20160693294


Residential

MAG NAIL IN U.P. #J3144 LOCATED ON THE N.E. CORNER OF W. BERKS ST. AND UPLAND WAY ELEV. = 191.00



# N. 59TH STREET

*→ BIKE LANE* → BAKE LANE



PECo 5"x5" Conduit, 2'-6" Cover-

BASE UNTIL REACHING ELEV. +190.00

- 45° BEND (TYP.)

— 12" PERFORATED PP

TOP ELEV. +190.00

**BOTTOM ELEV. +184.81** 

— 6" THICK SAND LAYER

**DISTRIBUTION PIPE @ 0.0% SLOPE** 

- CLEAN-WASHED AASHTO #57 STONE

AS INDICATED ON PLAN AND SECTION


WRAPPED IN GEOTEXTILE AND GEOMEMBRANE

4' X 6' TREE PIT (TYP.)

**OBSERVATION WELL** 


TOP OF STONE/GEOTEXTILE IN CARTWAY —

TO MATCH BOTTOM OF CONCRETE ROAD



#	COMPONENT ID	COMPONENT TYPE	PIPE LENGTH (FT)
1	G14290101-14-05	GREEN HWY GRATE INLET	N/A
2	G14290101-20-05	DISTRIBUTION PIPE	75
3	G14290101-21-05	UNDERDRAIN	43
4	G14290101-50-05	CLEANOUT	N/A
5	G14290101-50-10	CLEANOUT	N/A
6	G14290101-51-05	OBSERVATION WELL	N/A
7	G14290101-60-05	HWY GRATE INLET	N/A

# PROPOSED LEGEND



# NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST

HIGHWAY DISTRICT NO. SURVEY DISTRICT NO.

3 DAYS PRIOR TO EXCAVATION DRAINAGE SHT. NO. 33

OUTFALL NO. S-27/S-50 PA ONE CALL <u>20181993460</u>

OJECT. ENGR. PROJECT. ENGR. XXX XXXX

SUPERVISOR

# GREEN STORMWATER INFRASTRUCTURE PROJECT

UPLAND WAY GREENING GRADING & UTILITY PLAN - SYSTEM 1429-01 N. 59TH STREET

LANCASTER AVE. TO UPLAND WAY CITY OF PHILADELPHIA WATER DEPARTMENT CONSULTING ENGINEERING FIRM SCALES: 1"=10' PLAN **PROFILE** HORIZ. 1"=10' 1"=5' SECTION 1/4"=1WORK NO. S-50258-G

PHILADELPHIA WATER PLAN PREPARED FOR

THE CITY OF PHILADELPHIA

WATER DEPARTMENT BY:

**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

— Traffic Light (TO BE PROTECTED AND

CORED INTO INLET WITH SOLID CAP

SUPPORTED)

**TO SEWER** 

12" SOLID PP

**SYSTEM 1429-01** 

**ELEVATION VIEW** 

HORIZONTAL SCALE: 1" = 10'-0"

VERTICAL SCALE: 1" = 5'-0"

UNDERDRAIN @ 0.0% SLOPE

12" OUT INV. ELEV. +187.00

UNDERDRAIN @ 0.0% SLOPE

**GRATE ELEV. +190.00** 

TO TREE TRENCH

12" PERFORATED PP

4' GREEN HIGHWAY GRATE INLET

— 4' HIGHWAY GRATE INLET

**GRATE ELEV. +189.43** 12" IN INV. ELEV. +185.31

FROM TREE TRENCH

15" OUT INV. ELEV. +184.68

### ALL SIDEWALK AND CURBING TO BE REPLACED IN KIND ALONG FULL LIMITS OF CONSTRUCTION TO NEXT EXISTING JOINT OR AS DIRECTED BY PWD. 4. WELDED PIPE BOOT SEAL MUST BE INSTALLED AT ANY POINT WHERE A PIPE PENETRATES GEOMEMBRANE LINER. SUFFICIENT EROSION AND SEDIMENTATION CONTROL MEASURES WILL BE INSTALLED AND MAINTAINED BY THE CONTRACTOR AS TO PREVENT STANDING WATER OR SEDIMENTATION OF STORMWATER SYSTEMS. SYSTEMS DETERMINED BY PWD TO BE INADEQUATELY PROTECTED AND THEREBY COMPROMISED WILL BE REPLACED TO THE EXTENT REQUIRED BY PWD (UP TO AND INCLUDING FULL REPLACEMENT) AT NO ADDITIONAL COST TO PWD. ORIFICE SHOULD NOT BE DRILLED PRIOR TO AUTHORIZATION BY PWD. PWD WILL REVIEW THE RESULTS OF THE DOUBLE RING INFILTROMETER TESTS CONDUCTED AFTER SMP EXCAVATION AND WILL CONFIRM ORIFICE DIMENSIONS. . EROSION CONTROL MATTING SHALL BE PLACED OVER ALL SOIL SURFACES NOT STABILIZED BY PLANTING. 8. SUPPORT AND PROTECT ALL UTILITIES, UTILITY POLES, OVERHEAD WIRES, TRAFFIC SIGNAGE, TRAFFIC SIGNALS, AND STREET LIGHTING WITHIN THE LIMITS OF WORK.

ALL DISTANCES SHOWN ARE IN DISTRICT STANDARD MEASUREMENT. PAYMENT FOR

THE LOCATIONS AND ELEVATIONS OF THE EXISTING UTILITIES ARE APPROXIMATE. THE ELEVATIONS OF THE EXISTING UTILITIES MUST BE FIELD CHECKED DURING

OVERHEAD WIRES ON EAST SIDE OF N. 59TH STREET.


ALL WORK WILL BE BASED UPON THAT STANDARD.

GENERAL NOTES:


9. VERTICAL DATUM IS ON CITY OF PHILADELPHIA DATUM. 10. LINE AND GRADE STAKES FOR CURB, PAVING, ETC. WILL BE FURNISHED BY THE 7TH SURVEY DISTRICT OF THE CITY OF PHILADELPHIA. CONTACT INFORMATION: 7TH SURVEY DISTRICT, 6448 WOODLAND AVE, PHILA., PA, 19142, (215) 685-3052.

11. NOTIFY THE 7TH SURVEY DISTRICT A MINIMUM OF TWO (2) WEEKS PRIOR TO THE START OF WORK TO SCHEDULE A TIME FOR CURB STAKE LAYOUT SERVICES.

INSERT COMPANY LOGO DRAFT PRE-FINAL DESIGN AND ADDRESS HERE SUBMISSION <DATE>



PROPOSED LEGEND SYSTEM BOUNDARY **OVERHEAD WIRES CURB RAMP** N. 59TH STREET BIKE LANE DD **- S1429-01 S1429-02** - S1429-03 **∕**− S1429-04 C/K



TREE PIT CALIPER SIZE OVERHEAD WIRES COMMENTS **COMMON NAME BOTANICAL NAME LOCATION ID DIMENSIONS** Substitute with *Amelancher x grandiflora* Crataegus viridis 'Winter King' 2"-2 1/2" B&B S1429-01 Green Hawthorn 4' x 6' Yes 'Autumn Brilliance' if planted in the fall. Substitute with Amelancher x grandiflora S1429-02 Crataegus viridis 'Winter King' 2"-2 1/2" B&B Green Hawthorn 4' x 6' Yes 'Autumn Brilliance' if planted in the fall. Substitute with *Amelancher x grandiflora* 2"-2 1/2" B&B S1429-03 Crataegus viridis 'Winter King' Green Hawthorn 4' x 6' Yes 'Autumn Brilliance' if planted in the fall. Substitute with Amelancher x grandiflora Green Hawthorn Crataegus viridis 'Winter King' S1429-04 2"-2 1/2" B&B 4' x 6' Yes 'Autumn Brilliance' if planted in the fall.

NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST

3 DAYS PRIOR TO EXCAVATION

 HIGHWAY DISTRICT NO.
 01
 WARD NUMBER
 34/52

 DRAINAGE SHT. NO.
 33
 20181993459

 OUTFALL NO.
 S-27/S-50
 PA ONE CALL
 20181993460

CLEANOUT

**OBSERVATION WELL** 

**GREEN CITY INLET** 

OMG INLET

**GREEN HIGHWAY GRATE INLET** 

# GREEN STORMWATER INFRASTRUCTURE PROJECT

UPLAND WAY GREENING LANDSCAPE PLAN SYSTEM 1429-01

CITY OF PHILADELPHIA WATER DEPARTMENT CONSULTING ENGINEERING FIRM SCALES:

1/4"=1 PLAN

SUPERVISOR

ROJECT. ENGR. PROJECT. ENGR. XXX XXXX

WORK NO. S-50258-G

PHILADELPHIA WATER — DEPARTMENT — PLAN PREPARED FOR THE CITY OF PHILADELPHIA WATER DEPARTMENT BY:

INSERT COMPANY LOGO

EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

> DRAFT PRE-FINAL DESIGN AND ADDRESS HERE SUBMISSION <DATE>

5. PLANT SIZES IN THE PLANT SCHEDULE ARE TO BE CONSIDERED MINIMUM 6. THE PLANT SCHEDULE IDENTIFIES PLANT SPECIES AND QUANTITIES FOR EACH LOCATION. APPROXIMATE SPACING IS AS SHOWN ON THE PLANTING 7. IF REQUESTED BY PWD, THE CONTRACTOR SHALL ENSURE PLANTS ARE TAGGED FOR REVIEW AND APPROVAL BY PWD PRIOR TO ORDERING. APPROVAL OF PLANTS AT OFF-SITE LOCATIONS DOES NOT IMPLY FINAL APPROVAL OF PLANTS AT TIME OF DELIVERY OR AT THE TIME OF

1. ADJUST LOCATIONS OF PLANTS AS NECESSARY TO AVOID DAMAGE TO EXISTING UNDERGROUND UTILITIES AND EXISTING ABOVE GROUND ELEMENTS. ADJUSTMENTS SHALL BE COMPLETED AT CONTRACTOR'S EXPENSE AND SHALL

2. LANDSCAPE INSTALLATION SHALL BE COORDINATED WITH OTHER WORK AT

BE COORDINATED WITH THE PHILADELPHIA WATER DEPARTMENT (PWD).

3. ALL PLANTS SHALL BE IN FULL AND STRICT COMPLIANCE WITH THE

AMERICAN STANDARD FOR NURSERY STOCK (ANSI Z60.1-1996 OR LATER


4. LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR GRADING AND MAY BE REQUIRED TO PROVIDE ADDITIONAL SOIL. TOP OF MULCH ELEVATION SHALL

BE NO HIGHER THAN ELEVATION OF TOP OF ENERGY DISSIPATER.


INSTALLATION. 8. THE CONTRACTOR SHALL BE RESPONSIBLE FOR FURNISHING WATER AND HAND WATERING OF PLANTS AFTER INSTALLATION AND UP TO FINAL COMPLETION OF THE PROJECT, AND FOR THE MAINTENANCE PERIOD (SEE SPECIFICATIONS).


9. RESEED ALL DISTURBED AREAS.

GENERAL NOTES:



SCALE: N.T.S.





# GREEN STORMWATER INFRASTRUCTURE PROJECT

# BERKS & SEDGLEY GREENING LANDSCAPE PLAN STANDARD DETAILS

PHILADELPHIA

**EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION** THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

DRAFT SUBSTANTIALLY COMPLETE **DESIGN SUBMISSION < DATE>** 

PLAN PREPARED FOR THE CITY OF PHILADELPHIA WATER DEPARTMENT BY:

CITY OF PHILADELPHIA WATER DEPARTMENT

WORK NO. S-50179-G SHEET NO. L-X OF X SHEETS


PROJECT. ENGR. SUPERVISOR

XXX XXXX

DATE

CONTROLLING BENCH MARK

X—XUT ON HYDRANT RUM LOCATED ON THE N.W. CORNER OF LEON & FULLER ELEV. 84.12





EXAMPLE PLAN 2021 - NOT FOR CONSTRUCTION
THIS PLAN WAS DEVELOPED TO DEMONSTRATE DRAWING STANDARDS
AND MAY NOT REFLECT CURRENT DESIGN STANDARDS

DRAFT SUBSTANTIALLY COMPLETE

DESIGN SUBMISSION < DATE>

INSERT COMPANY LOGO AND ADDRESS HERE

# PROPOSED LEGEND

PERFORATED PIPE		OMG INLET
SOLID PIPE		HIGHWAY GRATE INLET
DRAINAGE AREA LIMIT		GREEN CITY INLET/ GREEN SHALLOW CITY INLET
STORMWATER TRENCH W/ GEOTEXTILE ON SIDES		GREEN HIGHWAY GRATE INLET
STORMWATER TRENCH		CONCRETE APRON
W/ GEOMEMBRANE LINER ON SIDES	#	TREE PIT
* * * GRASS STRIP	•	CLEANOUT
[ <del>* * * *</del> ]	0	OBSERVATION WELL

# NOTICE:

PURSUANT TO THE REQUIREMENTS OF PENNSYLVANIA ACT 50 (2017), THE CONTRACTOR SHALL CONTACT THE PENNSYLVANIA ONE CALL SYSTEM AT 1-800-242-1776, AT LEAST 3 DAYS PRIOR TO EXCAVATION

 HIGHWAY DISTRICT NO.
 06
 WARD NUMBER
 64

 SURVEY DISTRICT NO.
 04
 DRAINAGE SHT. NO.
 91
 20182554169

 OUTFALL NO.
 P-02
 PA ONE CALL
 20182553135

# GREEN STORMWATER INFRASTRUCTURE PROJECT

HOLMESBURG STREETS
DRAINAGE AREA MAP
FULLER STREET
TERRY ST. TO LEON ST.

CITY OF PHILADELPHIA WATER DEPARTMENT		
SCALES:		
PLAN	1"=20'	
•	WATER DEPARTMENT SCALES:	

WORK NO. S-50267-G SHEET NO. DA-2 OF 2 SHEETS